# RS 14 L

**SENSOR-SWITCHED INDOOR LIGHT**

EAN 4007841731113
E-Nr. 920622049

- Long-life aluminium enclosure
- High-quality opal glass shade
- max. of 5 lights can be interconnected by cable
- Impact-resistant material rated to IK07
- Facility for connecting fan

280 x 110 mm



# RS 14 L

**SENSOR-SWITCHED INDOOR LIGHT**

EAN **4007841731113**
E-Nr. **920622049**

# Technical Data

## DIMENSIONS

| | |
|---|---|
| Dimensions Ø × H | **280 x 110 mm** |

## ELECTRICAL

| | |
|---|---|
| Mains connection | **230 – 240 V , 50 / 50 Hz** |
| Power | **60 W** |
| Switching output 1 resistive | **800 W** |

## SENSOR TECHNOLOGY

| | |
|---|---|
| Sensor technology | **High frequency** |
| Transmission power | **< 1 mW** |
| With motion detector | **Yes** |
| Detection | **also through glass, wood and stud walls** |
| Detection angle | **360 °** |
| Opening angle | **160 °** |
| Electronic scalability | **Yes** |
| Mechanical scalability | **No** |

## CONNECTIVITY

| | |
|---|---|
| Control technology | **On/Off-Leuchte** |

## LIGHTING TECHNOLOGY

| | |
|---|---|
| With illuminant | **No** |
| Illuminant | **All-purpose lamp** |
| Base | **E27** |

## SETTINGS

| | |
|---|---|
| Twilight switch | **Yes** |
| Twilight setting | **2 – 2000 lx** |
| Time setting | **5 sec – 15 min** |

## HOUSING & MATERIAL

| | |
|---|---|
| Impact resistance | **IK07** |
| Protection class (IP) | **IP44** |
| Protection class | **II** |
| Ambient temperature | **-20 – 40 °C** |
| Housing material | **Aluminium** |
| Cover material | **Plastic, opal** |

## SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **5 years** |

# RS 14 L

**SENSOR-SWITCHED INDOOR LIGHT**

EAN **4007841731113**
E-Nr. **920622049**

## Accessories

### ORDERING INFORMATION

| | |
|---|---|
| Art.-Nr. | 4007841731113 |
| EAN | 4007841731113 |
| E-Number | 920622049 |
| Typ | **RS 14 L** |

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss