

elani P2400 TW

ELANI

neva
lux

Product code 221119

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

2400 x 60 x 80 mm



elani P2400 TW

Product code 221119

ELANI

Technical Data


DIMENSIONS			
Dimensions L x W x H	2400 x 60 x 80 mm		
Suspension length	2000 mm		
ELECTRICAL			
Mains connection	200...240 V / 50 – 60 Hz		
Power	74 W		
Replaceable driver	Yes		
Type of wiring	Suitable for through wiring		
SENSOR TECHNOLOGY			
With motion detector	No		
With light sensor	No		
LIGHTING TECHNOLOGY			
Colour temperature	3000...5600 K		
LED colour deviation	SDCM3		
Colour rendering index	80-89		
ILLUMINANT	Yes, LED-System		
Luminous flux	9600 lm (Down 6240, Up 3360)		
Beam angle	Down 105°, Up 115°		
Luminaire luminous efficacy	130 lm/W		
Glare value	UGR < 22		
LIFETIME			
LED lifespan (25 °C)	70000 h		
SETTINGS			
DALI dimming	Yes		
With emergency light	No		
Suitable for light band configuration	Yes		
Direct/indirect ratio separately controllable	Yes		
Constant light output control	Yes		
HOUSING & MATERIAL			
Protection class (IP)	IP20		
Protection class	II		
Ambient temperature	-20...45 °C		
Housing material	Aluminium		
Cover material	Acrylic glass opal		
Mounting type	Ceiling pendant		
Colour	Aluminium		
SCOPE OF DELIVERY & WARRANTY			
Manufacturer warranty	5 years		
CERTIFICATES & EPREL			
EPREL energy efficiency class	D		

elani P2400 TW

Product code 221119

ELANI

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221101	elani Diffusor 2500 CDP	Cover
 221108	Emergency Package 1h (Astra)	Emergency lighting
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221396	elani Color RAL_NCS_2400	Other
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221119

Typ

elani P2400 TW

nevalux

AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss