

nayo SN TW

NAYO CONNECT SN

neva
lux

Product code 220604

neva
lux

1203 x 52 x 1960 mm



nayo SN TW

NAYO CONNECT SN

Product code 220604

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		With switch	
Dimensions L x W x H	1203 x 52 x 1960 mm	Colour temperature	3000...6000 K		Yes
ELECTRICAL		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	Protection class (IP)	IP20
Power	80 W	Illuminant	LED	Protection class	I
Replaceable driver	Yes	Luminous flux	8000 lm (Down 2000, Up 6000)	Ambient temperature	-20...45 °C
LED rated current	450 mA / 1600 mA	Beam angle	Down 80°, Up 140°	Housing material	Aluminum
SENSOR TECHNOLOGY		Luminaire luminous efficacy	100 lm/W	Cover material	Darklight Optics
Sensor technology	passive infrared	Glare value	UGR < 12	Mounting type	Free standing floor
With motion detector	Yes	LIFETIME		Colour	white
Detection angle	360 °	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
Presence range	Ø 3 m	SETTINGS		Manufacturer warranty	5 years
With light sensor	Yes	Direct/indirect ratio separately controllable	Yes	CERTIFICATES & EPREL	
				EPREL energy efficiency class	F

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220175	nayo P 4K	
 220463	nayo P Diffused 4K	

ORDERING INFORMATION

Art.-Nr.

220604

Typ

nayo SN TW

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss