

sensiQ S KNX inox



Product code 4007841004040

E-Nr. 535941878

- 4x pyro system
- Remote control RC1 included

The logo for neva lux, with 'neva' in black and 'lux' in yellow.

128 x 74 x 114 mm



Technical Data

IDENTIFICATION		Range detail		Base light function	
Variant	inox	Reach adjustable from 2 - 20 m in 3 directions (100° in each)		Base light function time	Yes
Version	Motion detectors	Radial range	r = 4 m (42 m²)	Settings via	1-255 min
Type of accessory	Corner adapter	Tangential range	r = 20 m (1047 m²)	With remote control	ETS software, Remote control, Bus
Model	KNX	Switching zones	304 switching zones	Twilight setting teach	Yes
DIMENSIONS		Mounting height	2,00 – 5,00 m	HOUSING & MATERIAL	
Dimensions L x W x H	128 x 74 x 114 mm	Optimal mounting height	2 m	Protection class (IP)	IP54
ELECTRICAL		CONNECTIVITY		Ambient temperature	-20 – 50 °C
Supply voltage detail	KNX bus	Networking	Yes	Mounting location	corner wall
SENSOR TECHNOLOGY		KNX functions	Light output 2x, Presence output, Light level, Basic light level function, Photo-cell controller, Close range	Application location	Indoors Outdoors
Sensor technology	passive infrared	With bus coupler	Yes	Mounting type	Surface wiring
Detection angle	300 °	LIGHTING TECHNOLOGY		Material	Plastic
Opening angle	90 °	Constant light regulation	Yes	Colour	Stainless steel
Sneak-under protection	Yes	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
Segment-by-segment masking	Yes	Twilight setting	2 – 2000 lx	Manufacturer warranty	5 years
Electronic scalability	No	Time setting	5 sec – 15 min	CERTIFICATES & EPREL	
Mechanical scalability	Yes			Certificates	VDE

sensIQ S KNX inox

Product code **4007841004040**
E-Nr. **535941878**

Illustrations

MOUNTING HEIGHT

2,00 – 5,00 m BEREICH	2 m OPTIMAL
--------------------------	----------------

sensIQ S KNX inox

Product code **4007841004040**
E-Nr. **535941878**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841601416	Fernbedienung RC1	

ORDERING INFORMATION

Art.-Nr.

4007841004040

E-Number

535941878

Typ

sensIQ S KNX inox

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss