

PD-24 ECO KNX - in-ceiling installation, white

neva
lux**MOTION AND PRESENCE DETECTOR**

EAN 4007841088033

- Our series for the common ranges
- Presence detector with 24 m motion detection and 7.5 m presence detection for integration into a KNX bus system
- Ideal for large offices, meeting rooms or passageways
- Easy to mount due to magnetic holder and round design
- Starting the programming mode from a distance via Smart Remote remote control via app
- Including pluggable cover caps for detection limitation
- External approval and measurement according to sensNORM

● steinel

PD-24 ECO KNX - in-ceiling installation, white

MOTION AND PRESENCE DETECTOR

EAN 4007841088033

Technical Data

IDENTIFICATION		CONNECTIVITY		HOUSING & MATERIAL	
Version	Motion and Presence Detector	Type of networking	Master/master	Protection class (IP)	IP20
SENSOR TECHNOLOGY		Networking via	Cable	Ambient temperature	from -20 up to 50 °C
Max. mounting height	10,00 m	KNX functions	Light level Light output 2x Constant-lighting control Photo-cell controller Basic light level function HVAC output Logic gate Presence output Sabotage protection Day / night function	Housing material	Plastic
Sensor technology	passive infrared			Cover material	Other
With motion detector	Yes			Cover material (scope of delivery)	shrouds
Detection angle	360 °			Mounting location	ceiling
Segment-by-segment masking	Yes	With bus coupler	Yes	Application location	Indoors
Electronic scalability		SETTINGS		Mounting type	In-ceiling installation
Mechanical scalability	No	Twilight setting	2 – 800 lx	Material	Plastic
Radial range	Ø 5.5 m (24 m²)	Functions	Motions sensor Light sensor Presence function Presence detector logic	Application room	Indoors function room / ancillary room one-person office warehouse
Tangential range	Ø 24 m (452 m²)			Colour	white
Switching zones	1436 switching zones	Settings via	Bus ETS software Smart Remote	SCOPE OF DELIVERY & WARRANTY	
Mounting height	2 – 10,00 m	With remote control	No	Manufacturer warranty	5 years
Presence range	Ø 7.5 m (44 m²)			Corner wall bracket included	No
Optimal mounting height	2,8 m				

PD-24 ECO KNX - in-ceiling installation, white

MOTION AND PRESENCE DETECTOR

EAN 4007841088033

Illustrations

MOUNTING HEIGHT

2 – 10,00 m BEREICH	2,8 m OPTIMAL	10,00 m MAX
------------------------	------------------	----------------

PD-24 ECO KNX - in-ceiling installation, white

MOTION AND PRESENCE DETECTOR

EAN 4007841088033

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841079543	Deckeneinbau-Adapter Deckeneinbau	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592806	Nutzer Fernbedienung RC5	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

088033

EAN

4007841088033

Typ

PD-24 ECO KNX - in-ceiling installation, white

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss