IS 300 white

MOTION DETECTOR

EAN 4007841602215

- Wireless interconnection
- Including corner wall mount
- UV-resistant plastic

85 x 60 x 95 mm



IS 300 white

MOTION DETECTOR

EAN **4007841602215**

Technical Data

IDENTIFICATION

Variant	**white**
Version	**Motion detectors**

DIMENSIONS

Dimensions L × W × H	**85 x 60 x 95 mm**

ELECTRICAL

Mains connection	**230 – 240 V , 50 / 50 Hz**
Switching output 1 resistive	**2000 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**300 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 3 m (24 m²)**
Tangential range	**r = 12 m (377 m²)**
Switching zones	**456 switching zones**
Optimal mounting height	**2 m**

CONNECTIVITY

Networking	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Constant light regulation	**No**

SETTINGS

Twilight setting	**2 – 2000 lx**
Time setting	**10 sec – 15 min**
Base light function	**No**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP54**
Ambient temperature	**-20 – 50 °C**
Mounting location	**corner wall**
Application location	**Indoors Outdoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

IS 300 white

MOTION DETECTOR

EAN **4007841602215**

Illustrations

MOUNTING HEIGHT

2 m

OPTIMAL

IS 300 white

MOTION DETECTOR

EAN **4007841602215**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841630218	**Eckwandhalter 01 weiss**	Accessory
	4007841630119	**Eckwandhalter 01 schwarz**	Accessory

ORDERING INFORMATION

Art.-Nr.	4007841602215
EAN	4007841602215
Typ	**IS 300 white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss