

lisha V2 connect PIR P1200 4K

LISHA V2

neva
lux

Product code **221979**

- For universal use for illumination of offices, schools, traffic zones, etc.
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- Microprismatic diffuser for best possible glare control
- Link technology for seamless extension of the luminaire with continuous wiring
- Variants with 1.2 and 1.5 meter length available
- Housing Aluminium white

neva
lux

1218 x 60 x 80 mm



lisha V2 connect PIR P1200 4K

LISHA V2

Product code 221979

Technical Data

DIMENSIONS		With light sensor	Yes	Suitable for light band configuration	Yes
Dimensions L x W x H	1218 x 60 x 80 mm	CONNECTIVITY		Direct/indirect ratio separately controllable	No
Suspension length	1500 mm	With radio network control	Yes	With program-controlled lighting control	Yes
ELECTRICAL		LIGHTING TECHNOLOGY		Constant light output control	Yes
Mains connection	200...240 V / 50 – 60 Hz	Colour temperature	4000 K	HOUSING & MATERIAL	
Power	50 W	LED colour deviation	SDCM3	Protection class (IP)	IP20
Replaceable driver	Yes	Colour rendering index	80-89	Protection class	I
Type of wiring	Through wiring included	Illuminant	LED	Ambient temperature	-20...45 °C
LED rated current	1250 mA	Luminous flux	6500 lm (Down 1950, Up 4550)	Housing material	Aluminum
Maximum number of luminaires per circuit breaker	C10: 23x, C13: 30x, C16: 37x, C20: 47x, B10: 17x, B13: 22x, B16: 27x, B20: 34x	Beam angle	Down 90°, Up 110°	Cover material	Microprismatic acrylic glass
SENSOR TECHNOLOGY		Luminaire luminous efficacy	130 lm/W	Mounting type	Ceiling pendant
Sensor technology	passive infrared	Glare value	UGR < 19	Colour	white
With motion detector	Yes	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
Radial range	4 x 4 m (16 m²)	SETTINGS		CERTIFICATES & EPREL	
Tangential range	6 x 6 m (36 m²)	DALI dimming	Yes	EPREL energy efficiency class	D
Presence range	4 x 4 m (16 m²)	With emergency light	No		

lisha V2 connect PIR P1200 4K

LISHA V2

Product code 221979

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221642	lisha V2 Diffusor 1M	Cover
 221643	lisha V2 Link P	Coupler/connector straight
 221644	lisha V2 CBox Connect	Adapter
 221618	Emergency Package 1h (50V/3.5W)	Emergency lighting
 221570	Connect TK2 BLM	Pushbutton interface
 221591	Smartlink T-Board PB4	Wireless push-button
 221970	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2	Wireless push-button
 221971	Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4	Wireless push-button

ORDERING INFORMATION

Art.-Nr.

221979

Typ

lisha V2 connect PIR P1200 4K

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss