IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN 4007841049447
E-Nr. 535955367

124 x 78 mm



IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN 4007841049447
E-Nr. 535955367

Technical Data

IDENTIFICATION

Variant	LiveLink - concealed installation, round
Version	Motion detectors
Model	LiveLink

DIMENSIONS

Dimensions Ø × H	124 x 78 mm

ELECTRICAL

Mains connection	230 V, 50 / 60 Hz
Supply voltage detail	DALI bus
Livelink values	Light level, Motion detection, Presence detection

SENSOR TECHNOLOGY

Sensor technology	passive infrared
Detection angle	360 °
Opening angle	45 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	12 x 6 m (72 m²)
Tangential range	23 x 6 m (138 m²)
Switching zones	280 switching zones
Mounting height	2,50 – 5,00 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Number of DALI participants	3
Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

Constant light regulation	No

SETTINGS

Twilight setting	2 – 1000 lx
Time setting	5 sec – 15 min
Base light function	No
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	-20 – 50 °C
Mounting location	ceiling
Application location	Indoors Outdoors
Mounting type	Concealed wiring
Material	Plastic
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	corridor, aisle, underground car park, multi-storey car park

IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN **4007841049447**
E-Nr. **535955367**

Illustrations

MOUNTING HEIGHT

2,50 – 5,00 m BEREICH	2,8 m OPTIMAL

IS 345 LiveLink - concealed installation, round

MOTION DETECTOR

EAN **4007841049447**
E-Nr. **535955367**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841049447
EAN	4007841049447
E-Number	535955367
Typ	**IS 345 LiveLink - concealed installation, round**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss