L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841657512

- Optional basic lighting level 0 - 50 %
- UV-resistant plastic
- Intelligent soft light start
- 4-hour manual override (optional)

330 x 215 x 257 mm



L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841657512

Technical Data

IDENTIFICATION

Variant	Silver

DIMENSIONS

Dimensions L × W × H	330 x 215 x 257 mm

ELECTRICAL

Mains connection	230 – 240 V , 50 / 60 Hz
Power	60 W

SENSOR TECHNOLOGY

Sensor technology	passive infrared
With motion detector	Yes
Detection angle	240 °
Opening angle	120 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	r = 12 m (302 m²)
Tangential range	r = 12 m (302 m²)

CONNECTIVITY

Control technology	On/Off-Leuchte

LIGHTING TECHNOLOGY

With illuminant	No
Illuminant	All-purpose lamp
Base	E27
Soft light start	Yes
Continuous light	selectable, 4h

SETTINGS

Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 15 min
Base light function	Yes
Settings via	Potentiometers

HOUSING & MATERIAL

Impact resistance	IK00
Protection class (IP)	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Glass transparent

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	3 years

L 115 S Silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841657512**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841001681	**Ersatzglas für L 115 S**	Spare Part

ORDERING INFORMATION

Art.-Nr.	4007841657512
EAN	4007841657512
Typ	**L 115 S Silver**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss