

Hallway COM1 - Aufputz

HALLWAY

neva
lux

Product code 4007841057978

E-Nr. 535937002

- UV-resistant plastic
- Interconnectable and adjustable via Bluetooth

neva
lux

62 x 123 x 123 mm



Hallway COM1 - Aufputz

HALLWAY

Product code **4007841057978**
E-Nr. **535937002**

Technical Data

IDENTIFICATION	
Version	Presence detector
DIMENSIONS	
Dimensions L x W x H	62 x 123 x 123 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	2000 W
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	1000 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in µF	176 µF
Own consumption	1 W
Switching output 1 number of LED/fluorescent lamps	8 pcs.
Switching output 1 potential-free	No
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m

Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	25 x 3 m (75 m²)
Tangential range	25 x 3 m (75 m²)
Mounting height	2,00 – 4,00 m
Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master\nMaster/slave
Networking via	Bluetooth
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable
Constant light regulation	No

SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 2000 lx
Time setting	10 s – 60 Min.
Base light function	No
Main light adjustable	No
Functions	Group parameterisation\nSemi-/fully automatic\nLighting scenario\nManual ON / ON-OFF\nNeighbouring group function\nNormal / test mode
Settings via	Bluetooth
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL	
Protection class (IP)	IP54
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Surface wiring
Material	Plastic
Application room	Indoors corridor / aisle
Colour	white
RAL colour	9003

SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No

Hallway COM1 - Aufputz

HALLWAY

Product code 4007841057978

E-Nr. 535937002

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
---	-------------------------------------	----------------------------------

Hallway COM1 - Aufputz

HALLWAY

Product code **4007841057978**

E-Nr. **535937002**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841057978
E-Number	535937002
Typ	Hallway COM1 - Aufputz

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss