

IS 2180-5 inox

neva
lux

Product code **4007841605810**

E-Nr. **535940475**

- UV-resistant plastic
- Including corner wall mount

neva
lux

120 x 78 x 55 mm



IS 2180-5 inox

Product code **4007841605810**
E-Nr. **535940475**

Technical Data

IDENTIFICATION					
Variant	inox	Segment-by-segment masking	Yes	Time setting	5 sec – 15 min
Version	Motion detectors	Electronic scalability	No	Base light function	No
DIMENSIONS		Mechanical scalability	No	With remote control	No
Dimensions L x W x H	120 x 78 x 55 mm	Tangential range	r = 8 m (101 m²) / r = 20 m (628 m²)	Twilight setting teach	No
ELECTRICAL		Switching zones	504 switching zones	HOUSING & MATERIAL	
Mains connection	230 – 240 V , 50 / 50 Hz	Optimal mounting height	2 m	Protection class (IP)	IP54
Switching output 1 resistive	1000 W	CONNECTIVITY		Ambient temperature	-20 – 50 °C
SENSOR TECHNOLOGY		Networking	Yes	Mounting location	corner wall
Sensor technology	passive infrared	LIGHTING TECHNOLOGY		Application location	Outdoors
Detection angle	180 °	Constant light regulation	No	Mounting type	Surface wiring
Opening angle	90 °	SETTINGS		Material	Plastic
Sneak-under protection	Yes	Twilight setting	2 – 2000 lx	Colour	Silver
				SCOPE OF DELIVERY & WARRANTY	
				Manufacturer warranty	5 years

IS 2180-5 inox

Product code **4007841605810**
E-Nr. **535940475**

Illustrations

MOUNTING HEIGHT



IS 2180-5 inox

Product code **4007841605810**E-Nr. **535940475**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841605810
----------	---------------

E-Number	535940475
----------	-----------

Typ	IS 2180-5 inox
-----	-----------------------

**neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss