

XSolar SOL-0 silber



Product code **4007841052676**

E-Nr. **941200179**

- Including STEINEL LED system
- Intelligent soft light start
- High-quality monocrystalline solar panel
- Includes lithium iron-phosphate rechargeable battery
- High-quality aluminium
- House number illumination throughout the night

neva
lux

91 x 242 x 38 mm



XSolar SOL-O silber

Product code 4007841052676
E-Nr. 941200179

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	91 x 242 x 38 mm	Colour rendering index	80-89	Impact resistance	IK03
ELECTRICAL		With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP44
Power	0,07 W	Illuminant	LED cannot be replaced	Protection class	III
Supply voltage detail	Solar supply, no mains power required\nLithium-iron-phosphate rechargeable battery 2000 mAh	Base	without	Ambient temperature	-20 – 40 °C
SENSOR TECHNOLOGY		LED cooling system	Passive Thermo Control	Housing material	Aluminium
Max. mounting height	2,50 m	Soft light start	Yes	Cover material	Plastic, structured
Sensor technology	Light sensor	Efficiency without cover	100 lm/W	Mounting location	wall
With motion detector	No	LIFETIME		Application location	Outdoors
Mounting height	1,80 – 2,50 m	LED lifetime max. °C	50000 h	Mounting type	Surface wiring
LIGHTING TECHNOLOGY		Luminous flux decline per LM80	L70B10	Application room	courtyard & driveway front door outdoors
Measured luminous flux 360°	7 lm	SETTINGS		Colour	Silver
Colour temperature	3000 K	Twilight switch	Yes	SCOPE OF DELIVERY & WARRANTY	
LED colour deviation	SDCM5	Twilight setting	2 lx	Manufacturer warranty	3 years
		Base light function	Yes	CERTIFICATES & EPREL	
		Base light function time	all night	Certificates	GS
		Functions	Light sensor		
		Settings via	Potentiometers		

XSolar SOL-O silber

Product code **4007841052676**
E-Nr. **941200179**

Illustrations

MOUNTING HEIGHT

1,80 – 2,50 m BEREICH	2,50 m MAX
--------------------------	---------------

XSolar SOL-O silber

Product code **4007841052676**
E-Nr. **941200179**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841052676
E-Number	941200179
Typ	XSolar SOL-O silber
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	