

IR 180 UP easy Concealed wiring

MOTION DETECTOR

neva
lux

EAN 4007841055790

E-Nr. 535930900

- Infrared motion detector with 180° detection angle and up to 8 m detection range
- For flush-mounted wall installation indoors (IP 20), for easy retrofitting to automatic light in new and existing buildings (For 2- and 3-wire installation)
- Made of UV-resistant plastic for a long service life
- Stepless adjustment of time (5 sec. - 30 min.) and switch-on brightness (2-1000 lux), teach function, push-button for use as conventional light switch
- Reliably switches any light source with a total of max. 200 W switching load (LED light sources max. 160 W/50 pcs.)
- Incl. mounting accessories - plastic-free packaging

 **steinel**

57 x 81 x 81 mm



IR 180 UP easy Concealed wiring

MOTION DETECTOR

EAN 4007841055790

E-Nr. 535930900

Technical Data

IDENTIFICATION					
Version	Motion detectors	Sensor technology	passive infrared	Base light function	No
DIMENSIONS		With motion detector	Yes	Main light adjustable	No
Dimensions L x W x H	57 x 81 x 81 mm	Detection angle	180 °	Settings via	Potentiometers
ELECTRICAL		Opening angle	90 °	With remote control	No
Mains connection	220 – 240 V / 50 – 60 Hz	Sneak-under protection	Yes	Twilight setting teach	No
Power	200 W	Segment-by-segment masking	No	HOUSING & MATERIAL	
Switching output 1 resistive	200 W	Electronic scalability	No	Protection class (IP)	IP20
Fluorescent lamps ECG	150 W	Mechanical scalability	No	Ambient temperature	from 0 up to 40 °C
Fluorescent lamps uncompensated	150 VA	Radial range	r = 2 m (6 m²)	Housing material	Plastic
Fluorescent lamps series-compensated	150 VA	Tangential range	r = 8 m (101 m²)	Cover material	Plastic, structured
Fluorescent lamps parallel-compensated	150 VA	Switching zones	96 switching zones	Mounting location	wall
Switching output 1 low-voltage halogen lamps	200 VA	Mounting height	1,10 – 2,20 m	Application location	Indoors
LED lamps < 2 W	40 W	Optimal mounting height	1,1 m	Mounting type	Concealed wiring
LED lamps > 2 W < 8 W	100 W	CONNECTIVITY		Material	Plastic
LED lamps > 8 W	160 W	Networking	No	Application room	Indoors WC / washroom corridor / aisle function room / ancillary room kitchenette stairwell
Capacitive load in µF	132 µF	LIGHTING TECHNOLOGY		Colour	white
Switching output 1 number of LED/fluorescent lamps	4 pcs.	Soft light start	No	RAL colour	9010
SENSOR TECHNOLOGY		Continuous light	selectable	SCOPE OF DELIVERY & WARRANTY	
Max. mounting height	2,20 m	Constant light regulation	No	Manufacturer warranty	3 years
		SETTINGS		Corner wall bracket included	No
		Twilight switch	Yes	CERTIFICATES & EPREL	
		Twilight setting	2 – 1000 lx	Certificates	VDE
		Time setting	5 s – 30 Min.		

IR 180 UP easy Concealed wiring


MOTION DETECTOR

EAN 4007841055790

E-Nr. 535930900

Illustrations

TECHNICAL DRAWINGS



57 x 81 x 81 mm

MOUNTING HEIGHT

1,10 – 2,20 m BEREICH	1,1 m OPTIMAL	2,20 m MAX
--------------------------	------------------	---------------

IR 180 UP easy Concealed wiring


MOTION DETECTOR

EAN 4007841055790

E-Nr. 535930900


Wiring Diagrams

WIRING DIAGRAM 1



2-wire circuit diagram

WIRING DIAGRAM 2



3-wire circuit diagram

IR 180 UP easy Concealed wiring

MOTION DETECTOR

EAN 4007841055790

E-Nr. 535930900

Highlights



2 or 3-wire installation

IR 180 UP easy Concealed wiring

MOTION DETECTOR

EAN 4007841055790

E-Nr. 535930900

Accessories

ORDERING INFORMATION

Art.-Nr.	055790
EAN	4007841055790
E-Number	535930900
Typ	IR 180 UP easy Concealed wiring

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss