

elani P1500 3K

ELANI

neva
lux

Product code 221122

- For universal use for lighting offices, schools, traffic zones etc.
- Direct and indirect light can be controlled separately
- Dimmable DALI
- Variants with 1.5, 2.4 and 3.14 meter length available
- Housing Anodised aluminium
- Swiss Made

neva
lux

1500 x 60 x 80 mm



elani P1500 3K

ELANI

Product code 221122

Technical Data

DIMENSIONS		Colour rendering index		80-89	Constant light output control		No
Dimensions L x W x H		1500 x 60 x 80 mm					
Suspension length		2000 mm					
ELECTRICAL		Illuminant		Yes, LED-System	HOUSING & MATERIAL		
Mains connection		200...240 V / 50 – 60 Hz			Protection class (IP)		IP20
Power		47 W			Protection class		II
Replaceable driver		Yes			Ambient temperature		-20...45 °C
Type of wiring		Suitable for through wiring			Housing material		Aluminium
SENSOR TECHNOLOGY		Luminaire luminous efficacy		128 lm/W	Cover material		Acrylic glass opal
With motion detector		Yes			Mounting type		Ceiling pendant
With light sensor		No			Colour		Aluminium
LIGHTING TECHNOLOGY		Glare value		UGR < 22	SCOPE OF DELIVERY & WARRANTY		
Colour temperature		3000 K			Manufacturer warranty		5 years
LED colour deviation		SDCM3			CERTIFICATES & EPREL		
		LIFETIME			EPREL energy efficiency class		D
		LED lifespan (25 °C)		70000 h			
		SETTINGS					
		DALI dimming		Yes			
		With emergency light		No			
		Suitable for light band configuration		Yes			
		Direct/indirect ratio separately controllable		Yes			

elani P1500 3K

ELANI

Product code 221122

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221100	elani Diffusor 1500 CDP	Cover
 221343	elani Connector 90°	Coupler/connector L-shape
 221107	elani Link	Coupler/connector straight
 221106	elani Color RAL_NCS_1500	Other
 221996	elani WM-Set 2B	Mounting kit

ORDERING INFORMATION

Art.-Nr.

221122

Typ

elani P1500 3K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss