

imani B2000 4K DALI



Product code **221498**

- The universal trunking insert imani from nevalux is designed for professional refurbishment of existing trunking with T5 or T8 fluorescent tubes. The luminaire uses the existing trunking installation including existing through-wiring. Old light modules can be replaced with new modules easily, quickly and without tools. The insert fits most trunking systems available on the market.

neva
lux

2025 x 65 x 30 mm



imani B2000 4K DALI

Product code 221498

Technical Data

DIMENSIONS		LIGHTING TECHNOLOGY		Suitable for light band configuration	Yes
Dimensions L x W x H	2025 x 65 x 30 mm	Colour temperature	4000 K		
ELECTRICAL		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Mains connection	200...240 V / 50 – 60 Hz	Colour rendering index	80-89	Protection class (IP)	IP40
Power	68 W	Illuminant	LED	Protection class	I
Replaceable driver	Yes	Luminous flux	8626 lm	Ambient temperature	-20...45 °C
Type of wiring	Suitable for through wiring	Beam angle	105°	Housing material	Aluminum
LED rated current	390 mA	Luminaire luminous efficacy	127 lm/W	Cover material	Diffusor opal
Maximum number of luminaires per circuit breaker	C10: 16x, C16: 26x, B10: 10x, B16: 16x	Glare value	UGR < 24	Mounting type	Use in continuous row
SENSOR TECHNOLOGY		LIFETIME		Colour	white
With motion detector	No	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	SETTINGS		Manufacturer warranty	5 years
		DALI dimming	Yes	CERTIFICATES & EPREL	
		With emergency light	No	EPREL energy efficiency class	D

imani B2000 4K DALI

Product code 221498

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220688	Emergency Package 1h (250V/3.5W)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

221498

Typ

imani B2000 4K DALI

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss