

IS 3180 LiveLink - Aufputz eckig



Product code 4007841049409

E-Nr. 535941866

- UV-resistant plastic
- Optional corner wall mount bracket

neva
lux

95 x 95 x 65 mm



IS 3180 LiveLink - Aufputz eckig

Product code 4007841049409
E-Nr. 535941866

Technical Data

IDENTIFICATION		Mechanical scalability		No	With remote control		No
Variant	LiveLink - surface-mounted, square	Tangential range	r = 8 m (101 m²) / r = 20 m (628 m²)		Twilight setting teach		Yes
Version	Motion detectors	Switching zones	448 switching zones		HOUSING & MATERIAL		
Model	LiveLink	Mounting height	1,80 – 2,50 m		Protection class (IP)	IP54	
DIMENSIONS		Optimal mounting height	2 m		Ambient temperature	-20 – 50 °C	
Dimensions L × W × H	95 x 95 x 65 mm	CONNECTIVITY			Mounting location	corner wall	
ELECTRICAL		Networking	Yes		Application location	Indoors Outdoors	
Mains connection	230 V, 50 / 60 Hz	Number of DALI participants	3		Mounting type	Surface wiring	
Supply voltage detail	DALI bus	LIGHTING TECHNOLOGY			Material	Plastic	
SENSOR TECHNOLOGY		Constant light regulation	No		Colour	white	
Sensor technology	passive infrared	SETTINGS			RAL colour	9003	
Detection angle	180 °	Twilight setting	2 – 1000 lx		SCOPE OF DELIVERY & WARRANTY		
Opening angle	90 °	Time setting	5 sec – 15 min		Manufacturer warranty	5 years	
Sneak-under protection	Yes	Base light function	No		OTHER		
Segment-by-segment masking	Yes	Settings via	LiveLink app		Application, location, room	corridor, aisle, stairwell, multi-storey car park, underground car park	
Electronic scalability	No						

IS 3180 LiveLink - Aufputz eckig

Product code 4007841049409
E-Nr. 535941866

Illustrations

MOUNTING HEIGHT

1,80 – 2,50 m BEREICH	2 m OPTIMAL
--------------------------	----------------

IS 3180 LiveLink - Aufputz eckig

Product code **4007841049409**
E-Nr. **535941866**

Accessories

ORDERING INFORMATION	
Art.-Nr.	4007841049409
E-Number	535941866
Typ	IS 3180 LiveLink - Aufputz eckig
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	