Light Sensor Dual LiveLink - surface-mounted, square

PHOTO-CELL CONTROLLER

EAN 4007841009762

95 x 95 x 54 mm



Light Sensor Dual LiveLink - surface-mounted, square

PHOTO-CELL CONTROLLER

EAN 4007841009762

Technical Data

IDENTIFICATION

Variant	LiveLink - surface-mounted, square
Version	Constant-lighting controller
Model	LiveLink

DIMENSIONS

Dimensions L × W × H	95 x 95 x 54 mm

ELECTRICAL

Mains connection	16 V
Supply voltage detail	DALI bus
Livelink values	Light level directed & diffuse

SENSOR TECHNOLOGY

Sensor technology	Light sensor

CONNECTIVITY

Number of DALI participants	3
Control technology	On/Off-Leuchte

SETTINGS

Twilight setting	2 – 1000 lx
Settings via	LiveLink app

HOUSING & MATERIAL

Protection class (IP)	IP54
Ambient temperature	-20 – 50 °C
Mounting location	ceiling wall
Application location	Indoors Outdoors
Mounting type	Surface wiring
Material	Plastic
Colour	white
RAL colour	9010

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years

OTHER

Application, location, room	One-person office, classroom, Open-plan office, high-bay warehouse, conference room

Light Sensor Dual LiveLink - surface-mounted, square

EAN 4007841009762

PHOTO-CELL CONTROLLER

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841009762
EAN	4007841009762
Typ	**Light Sensor Dual LiveLink - surface-mounted, square**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss