

RS PRO P1 SP warmweiss

P-SERIE

neva
lux

Product code **221803**

- Including STEINEL LED system
- Intelligent soft light start
- Interconnectable by cable (maximum of 10 units)

neva
lux

280 x 110 mm



RS PRO P1 SP warmweiss

P-SERIE

Product code 221803

Technical Data

DIMENSIONS		With illuminant	Yes, STEINEL LED system	Protection class (IP)	IP54
Dimensions Ø x H	280 x 110 mm	Illuminant	LED cannot be replaced	Protection class	II
ELECTRICAL		Base	without	Ambient temperature	from -10 up to 40 °C
Mains connection	220 – 240 V / 50 – 60 Hz	LED cooling system	Passive Thermo Control	Housing material	Plastic
Power	8,3 W	Soft light start	Yes	Cover material	Plastic, opal
SENSOR TECHNOLOGY		LIFETIME		Mounting location	ceiling wall
With motion detector	No	LED lifetime max. °C	50000 h	Colour	white
CONNECTIVITY		LED lifetime L70B50 25°C	> 60000 h	SCOPE OF DELIVERY & WARRANTY	
Networking via	Cable	Luminous flux decline per LM80	L80B10	Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		SETTINGS		CERTIFICATES & EPREL	
Measured luminous flux 360°	953 lm	Main light adjustable	No	Certificates	DEKRA
Colour temperature	3000 K	HOUSING & MATERIAL		EPREL category	Surrounded product with integrated light source
		Impact resistance	IK03		

RS PRO P1 SP warmweiss

P-SERIE

Product code 221803

Accessories

ORDERING INFORMATION	
Art.-Nr.	221803
Typ	RS PRO P1 SP warmweiss
neva lux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	