L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841068899

- Outdoor light with motion detector and pleasant ambient light on the house wall
- High-quality aluminium screen as well as UV-resistant material for a long service life
- Automatic light thanks to 180 ° Infrared sensor with up to 10 m detection of movement
- Detection area and range can be individually limited using the cover stickers supplied and the swivelling sensor (90° vertical)
- With E27 socket for energy-saving lamps or LED bulbs with max. 15 W (not included in delivery)
- Incl. mounting accessories - plastic-free packaging

steinel

108 x 122 x 261 mm



L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841068899**

Technical Data

DIMENSIONS

Dimensions L × W × H	**108 x 122 x 261 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**15 W**

SENSOR TECHNOLOGY

Max. mounting height	**3,00 m**
Sensor technology	**passive infrared**
With motion detector	**Yes**
Detection angle	**180 °**
Sneak-under protection	**No**
Segment-by-segment masking	**No**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 3 m (14 m²)**
Tangential range	**r = 10 m (157 m²)**
Mounting height	**1,80 – 3 m**
Optimal mounting height	**2 m**

CONNECTIVITY

Networking	**No**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

With illuminant	**No**
Base	**E27**
Soft light start	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**8 s – 35 Min.**
Base light function	**No**
Main light adjustable	**No**
Settings via	**Potentiometers**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Impact resistance	**IK07**
Protection class (IP)	**IP44**
Protection class	**II**
Ambient temperature	**from -20 up to 40 °C**
Housing material	**Plastic**
Cover material	**Plastic, opal**
Cover material (scope of delivery)	**sticker**
Mounting location	**wall**
Application location	**Outdoors**
Mounting type	**Surface wiring**
Application room	**all round the building courtyard & driveway front door garden terrace / balcony**
Colour	**Anthracite**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**
House number sheet included	**No**

CERTIFICATES & EPREL

Certificates	**DEKRA**
EPREL category	**Surrounded product with separate light source (e.g. E27)**


L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841068899

Illustrations

TECHNICAL DRAWINGS



108 x 122 x 261 mm

MOUNTING HEIGHT

1,80 – 3 m	2 m	3,00 m
BEREICH	OPTIMAL	MAX


L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841068899

Wiring Diagrams

WIRING DIAGRAM 1




Circuit diagram

L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841068899

Highlights



High-quality aluminium trim panel



UV-resistant plastic

L 30 S with motion detector

E27 SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841068899**

Accessories

ORDERING INFORMATION

Art.-Nr.	068899
EAN	4007841068899
Typ	**L 30 S with motion detector**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss