

RS PRO P3 SP warmweiss

P-SERIE

neva
lux

Product code **221814**

- Including STEINEL LED system
- Intelligent soft light start
- Interconnectable by cable (maximum of 10 units)

neva
lux

400 x 142 mm



RS PRO P3 SP warmweiss

P-SERIE

Product code 221814

Technical Data

DIMENSIONS					
Dimensions Ø x H	400 x 142 mm	Colour temperature	3000 K	Protection class (IP)	IP54
ELECTRICAL		With illuminant	Yes, STEINEL LED system	Protection class	II
Mains connection	220 – 240 V / 50 – 60 Hz	Illuminant	LED cannot be replaced	Ambient temperature	from -10 up to 40 °C
Power	17,8 W	Base	without	Housing material	Plastic
SENSOR TECHNOLOGY		LED cooling system	Passive Thermo Control	Cover material	Plastic, opal
With motion detector	No	Soft light start	Yes	Mounting location	ceiling wall
CONNECTIVITY		LIFETIME		Colour	white
Networking via	Cable	LED lifetime max. °C	50000 h	SCOPE OF DELIVERY & WARRANTY	
LIGHTING TECHNOLOGY		LED lifetime L70B50 25°C	> 60000 h	Manufacturer warranty	5 years
Measured luminous flux 360°	2081 lm	Luminous flux decline per LM80	L80B10	CERTIFICATES & EPREL	
		HOUSING & MATERIAL		Certificates	DEKRA
		Impact resistance	IK03	EPREL category	Surrounded product with integrated light source

RS PRO P3 SP warmweiss

Product code **221814**

P-SERIE

Accessories

ORDERING INFORMATION

Art.-Nr. 221814

Typ RS PRO P3 SP warmweiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss