

# HF 3360 KNX - Aufputz rund

**neva**  
**lux**

Product code 4007841058234

E-Nr. 535945076

- UV-resistant plastic
- Large terminal compartment
- Optional remote controls
- Smart Remote remote control optional

**neva**  
**lux**

126 x 52 mm



# HF 3360 KNX - Aufputz rund

Product code **4007841058234**

E-Nr. **535945076**

## Technical Data

|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  |                                                                                                    |  |
|----------------------------|--|-----------------------------------------|--|---------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------|--|
| IDENTIFICATION             |  | Mounting height                         |  | 2,00 – 4,00 m             |  | Main light adjustable                                                                                                                                                      |  | 0 - 100 %                                                                                          |  |
| Version                    |  | Motion detectors                        |  | Optimal mounting height   |  | 2,8 m                                                                                                                                                                      |  | Settings via                                                                                       |  |
| DIMENSIONS                 |  |                                         |  | CONNECTIVITY              |  |                                                                                                                                                                            |  | ETS software\nRemote control\nBus\nSmart Remote                                                    |  |
| Dimensions Ø × H           |  | 126 x 52 mm                             |  | Networking                |  | Yes                                                                                                                                                                        |  | With remote control                                                                                |  |
| ELECTRICAL                 |  |                                         |  | Type of networking        |  | Master/slave                                                                                                                                                               |  | Twilight setting teach                                                                             |  |
| Supply voltage detail      |  | KNX bus                                 |  | Networking via            |  | KNX bus                                                                                                                                                                    |  | Yes                                                                                                |  |
| SENSOR TECHNOLOGY          |  |                                         |  | KNX functions             |  | Photo-cell controller\nBasic light level function\nLight level\nHVAC output\nConstant-lighting control\nLight output 2x\nPresence output\nDay / night function\nLogic gate |  | HOUSING & MATERIAL                                                                                 |  |
| Max. mounting height       |  | 4,00 m                                  |  | With bus coupler          |  | Yes                                                                                                                                                                        |  | Protection class (IP)                                                                              |  |
| Sensor technology          |  | High frequency                          |  | LIGHTING TECHNOLOGY       |  |                                                                                                                                                                            |  | IP54                                                                                               |  |
| Transmission power         |  | < 1 mW                                  |  | Soft light start          |  | Yes                                                                                                                                                                        |  | Ambient temperature                                                                                |  |
| HF technology              |  | 5,8 GHz                                 |  | Continuous light          |  | selectable                                                                                                                                                                 |  | from -20 up to 50 °C                                                                               |  |
| Detection                  |  | also through glass, wood and stud walls |  | Constant light regulation |  | Yes                                                                                                                                                                        |  | Mounting location                                                                                  |  |
| Detection angle            |  | 360 °                                   |  | SETTINGS                  |  |                                                                                                                                                                            |  | ceiling corner wall                                                                                |  |
| Opening angle              |  | 180 °                                   |  | Twilight switch           |  | Yes                                                                                                                                                                        |  | Application location                                                                               |  |
| Sneak-under protection     |  | Yes                                     |  | Twilight setting          |  | 2 – 1000 lx                                                                                                                                                                |  | Indoors                                                                                            |  |
| Segment-by-segment masking |  | No                                      |  | Time setting              |  | 5 s – 15 Min.                                                                                                                                                              |  | Mounting type                                                                                      |  |
| Electronic scalability     |  | Yes                                     |  | Base light function       |  | Yes                                                                                                                                                                        |  | Surface wiring                                                                                     |  |
| Mechanical scalability     |  | No                                      |  |                           |  |                                                                                                                                                                            |  | Material                                                                                           |  |
| Radial range               |  | Ø 8 m (50 m²)                           |  |                           |  |                                                                                                                                                                            |  | Plastic                                                                                            |  |
| Tangential range           |  | Ø 8 m (50 m²)                           |  |                           |  |                                                                                                                                                                            |  | Application room                                                                                   |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | Colour                                                                                             |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | white                                                                                              |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | RAL colour                                                                                         |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | 9003                                                                                               |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | SCOPE OF DELIVERY & WARRANTY                                                                       |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | Manufacturer warranty                                                                              |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | 5 years                                                                                            |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | Corner wall bracket included                                                                       |  |
|                            |  |                                         |  |                           |  |                                                                                                                                                                            |  | No                                                                                                 |  |

HF 3360 KNX - Aufputz rund

Product code **4007841058234**  
E-Nr. **535945076**

Illustrations

MOUNTING HEIGHT

|                          |                  |               |
|--------------------------|------------------|---------------|
| 2,00 – 4,00 m<br>BEREICH | 2,8 m<br>OPTIMAL | 4,00 m<br>MAX |
|--------------------------|------------------|---------------|

HF 3360 KNX - Aufputz rund

Product code **4007841058234**  
E-Nr. **535945076**

Accessories

| ARTICLE NUMBER                                                                                    | DESCRIPTION                                   | CATEGORY  |
|---------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------|
|  4007841009151   | Smart Remote                                  | Accessory |
|  4007841593018    | Service Fernbedienung RC6 KNX                 | Other     |
|  4007841592912    | Nutzer Fernbedienung RC7 KNX                  | Accessory |
|  4007841056698    | Schwarze Blende für den HF 3360 Aufputz rund  | Coverage  |
|  4007841056674 | Schwarze Blende für den HF 3360 Aufputz eckig | Coverage  |

ORDERING INFORMATION

Art.-Nr.

4007841058234

E-Number

535945076

Typ

HF 3360 KNX - Aufputz rund

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss