

lisha W1200 4K



Product code **221378**

- For universal use in lighting offices, schools, lobbies, traffic zones, etc.
- Convincing concept for simple and fast mounting
- Link technology for seamless extension of the continuous row with through-wiring
- Dimmable DALI
- Variants with 0.6, 1.2 and 1.8 meter length available
- Housing Aluminum White

neva
lux

1210 x 51 x 85 mm



lisha W1200 4K

Product code 221378


Technical Data

DIMENSIONS		Colour rendering index		80-89	HOUSING & MATERIAL				
Dimensions L x W x H		1210 x 51 x 85 mm		Illuminant		Yes, LED-System	Protection class (IP)		IP20
ELECTRICAL				Luminous flux		3900 lm (Down 1950, Up 1950)	Protection class		I
Mains connection		200...240 V / 50 – 60 Hz		Beam angle		15° Wallwasher	Ambient temperature		-20...45 °C
Power		30 W		Luminaire luminous efficacy		130 lm/W	Housing material		Aluminium
Replaceable driver		Yes		Glare value		UGR < 19	Cover material		Microprismatic acrylic glass
Type of wiring		Through wiring included		LIFETIME			Mounting type		Wall surface-mounted
SENSOR TECHNOLOGY				LED lifespan (25 °C)		50000 h	COLOUR		white
With motion detector		No		SETTINGS			SCOPE OF DELIVERY & WARRANTY		
With light sensor		No		DALI dimming		Yes	Manufacturer warranty		5 years
LIGHTING TECHNOLOGY				With emergency light		No	CERTIFICATES & EPREL		
Colour temperature		4000 K		Suitable for light band configuration		Yes	EPREL energy efficiency class		D
LED colour deviation		SDCM3							

lisha W1200 4K

Product code 221378

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220176	lisha C1200 4K	
 220178	lisha C1200 Wallwasher 4K	
 220180	lisha P1200 4K	
 220182	lisha P1200 Wallwasher 4K	

ORDERING INFORMATION

Art.-Nr.

221378

Typ

lisha W1200 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss