

True Presence BT IPD - concealed

PRESENCE DETECTOR

neva
lux

EAN 4007841085506

E-Nr. 535903095

● steinel

50 x 103 x 103 mm



True Presence BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841085506
E-Nr. 535903095

Technical Data

IDENTIFICATION					
Version	Presence detector	Radial range	Ø 15 m (177 m²)	Twilight setting teach	No
DIMENSIONS		Tangential range	Ø 15 m (177 m²)	HOUSING & MATERIAL	
Dimensions L x W x H	50 x 103 x 103 mm	Mounting height	2,00 – 12,00 m	Protection class (IP)	IP20
ELECTRICAL		Presence range	Ø 15 m (177 m²)	Ambient temperature	from -20 up to 50 °C
Mains connection	220 – 240 V / 50 – 60 Hz	True Presence range	Ø 9 m (64 m²)	Mounting location	ceiling
SENSOR TECHNOLOGY		Optimal mounting height	2,8 m	Application location	Indoors
Max. mounting height	12,00 m	CONNECTIVITY		Mounting type	Concealed wiring
Sensor technology	High frequency	Networking	Yes	Material	Plastic
Transmission power	< 1 mW	Type of networking	Master/slave	Application room	Indoors WC / washroom care room changing room classroom conference room / meeting room dining hall / staff restaurant duty room high-bay warehouse hotel room kitchenette lecture hall one-person office open-plan office production facilities reception / lobby recreation room sports hall warehouse
HF technology	7,2 GHz	Networking via	Bluetooth Mesh	Colour	white
With motion detector	Yes	LIGHTING TECHNOLOGY		RAL colour	9003
Detection	also through glass, wood and stud walls	Soft light start	No	SCOPE OF DELIVERY & WARRANTY	
Detection angle	360 °	Continuous light	selectable	Manufacturer warranty	5 years
Opening angle	160 °	Constant light regulation	No	Corner wall bracket included	No
Sneak-under protection	Yes	SETTINGS			
Segment-by-segment masking	No	Twilight switch	No		
Electronic scalability	Yes	Twilight setting	2 – 2000 lx		
Mechanical scalability	No	Base light function	No		
		Main light adjustable	No		
		Settings via	Bluetooth Mesh		
		With remote control	No		


True Presence BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841085506
E-Nr. 535903095

Illustrations

TECHNICAL DRAWINGS



50 x 103 x 103 mm

MOUNTING HEIGHT

2,00 – 12,00 m BEREICH	2,8 m OPTIMAL	12,00 m MAX
---------------------------	------------------	----------------


True Presence BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841085506
E-Nr. 535903095

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram

True Presence BT IPD - concealed

PRESENCE DETECTOR


EAN 4007841085506

E-Nr. 535903095

Highlights



UV-resistant plastic



Digital high frequency sensor

True Presence BT IPD - concealed

PRESENCE DETECTOR

EAN 4007841085506

E-Nr. 535903095

Accessories

ORDERING INFORMATION	
Art.-Nr.	085506
EAN	4007841085506
E-Number	535903095
Typ	True Presence BT IPD - concealed

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss