

IR Quattro HD LiveLink

neva
lux

Product code **4007841009717**

E-Nr. **535930307**

- 4 pyros with DSP (Digital Signal Processing)
- Optional surface-mounting adapter (IP 54, KNX)
- Optional guard cage
- Settings via LiveLink app

neva
lux

120 x 120 x 50 mm



IR Quattro HD LiveLink

Product code **4007841009717**
E-Nr. **535930307**

Technical Data

IDENTIFICATION					
Variant	LiveLink	Electronic scalability	No	With remote control	No
Version	Presence detector	Mechanical scalability	Yes	Twilight setting teach	Yes
Model	LiveLink	Radial range	8 x 8 m (64 m²)	HOUSING & MATERIAL	
DIMENSIONS		Tangential range	20 x 20 m (400 m²)	Protection class (IP)	IP20
Dimensions L x W x H	120 x 120 x 50 mm	Switching zones	4800 switching zones	Mounting location	ceiling
ELECTRICAL		Mounting height	2,50 – 10,00 m	Application location	Indoors
Livelihood values	Light level, Motion detection	Presence range	8 x 8 m (64 m²)	Mounting type	Concealed wiring
SENSOR TECHNOLOGY		Optimal mounting height	2,8 m	Material	Plastic
Sensor technology	passive infrared	CONNECTIVITY		Colour	white
Detection angle	360 °	Number of DALI participants	3	RAL colour	9010
Opening angle	160 °	With bus coupler	Yes	SCOPE OF DELIVERY & WARRANTY	
Sneak-under protection	Yes	SETTINGS		Manufacturer warranty	5 years
Segment-by-segment masking	No	Time setting	30 sec – 60 min	OTHER	
		Settings via	LiveLink app	Application, location, room	Open-plan office, high-bay warehouse, conference room, sports hall, classroom

Illustrations

MOUNTING HEIGHT

2,50 – 10,00 m BEREICH	2,8 m OPTIMAL
---------------------------	------------------

IR Quattro HD LiveLink

Product code **4007841009717**
E-Nr. **535930307**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841009717

E-Number

535930307

Typ

IR Quattro HD LiveLink

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss