L 625 LED aluminium silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841053147

- Including STEINEL LED system
- Intelligent soft light start
- Optional basic lighting level 25 %
- Including sheet of self-adhesive house numbers
- Sensor with 4 intelligent programmes
- High-quality aluminium
- UV resistant material

122 x 232 x 269 mm



L 625 LED aluminium silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN **4007841053147**

Technical Data

IDENTIFICATION

Variant	**aluminium silver**

DIMENSIONS

Dimensions L × W × H	**122 x 232 x 269 mm**

ELECTRICAL

Mains connection	**220 – 240 V , 50 / 60 Hz**
Power	**10 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**90 °**
Sneak-under protection	**Yes**
Tangential range	**r = 7 m (154 m²)**

CONNECTIVITY

Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Efficiency	**65 lm/W**
Colour temperature	**3000 K**
LED colour deviation	**SDCM3**
Colour rendering index	**80-89**
Soft light start	**Yes**
Continuous light	**selectable, 4h**
Luminous flux	**655 lm**

LIFETIME

LED lifetime max. °C	**50000 h**

SETTINGS

Twilight setting	**2 – 1000 lx**
Time setting	**5 sec – 15 min**

HOUSING & MATERIAL

Protection class (IP)	**IP44**
Protection class	**I**
Ambient temperature	**-20 – 50 °C**

L 625 LED aluminium silver

SENSOR-SWITCHED OUTDOOR LIGHT

EAN 4007841053147

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841006310	**LED Ersatzpanel für L 270 / L 625 / L 665**	Spare Part
	4007841006365	**Ersatzglas für L 270 / L 625 / L 626**	Spare Part
	4007841009038	**Ersatz-Minisensor silber**	Spare Part

ORDERING INFORMATION

Art.-Nr.	4007841053147
EAN	4007841053147
Typ	**L 625 LED aluminium silver**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss