

IR Quattro 8m KNX - in-ceiling installation

neva
lux**PRESENCE DETECTOR**

EAN 4007841079390

E-Nr. 535934708

 **steinel**

113 x 120 x 120 mm



IR Quattro 8m KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079390

E-Nr. 535934708

Technical Data

IDENTIFICATION	
Version	Presence detector
DIMENSIONS	
Dimensions L x W x H	113 x 120 x 120 mm
SENSOR TECHNOLOGY	
Max. mounting height	8,00 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360 °
Opening angle	100 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	No
Mechanical scalability	Yes
Radial range	5 x 5 m (25 m²)
Tangential range	7 x 7 m (49 m²)
Switching zones	1760 switching zones
Mounting height	2,50 – 8,00 m
Presence range	4 x 4 m (16 m²)

Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master Master/slave
Networking via	KNX bus
KNX functions	Photo-cell controller Basic light level function Light level HVAC output Constant-lighting control Light output 4x Presence output Day / night function Logic gate
With bus coupler	Yes
LIGHTING TECHNOLOGY	
Soft light start	Yes
Continuous light	selectable
Constant light regulation	Yes
SETTINGS	
Twilight switch	Yes
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Base light function	Yes

Main light adjustable	0 - 100 %
Settings via	ETS software Remote control Bus Smart Remote
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	from 0 up to 40 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors changing room conference room / meeting room duty room function room / ancillary room kitchenette one-person office recreation room
Colour	white
RAL colour	9010
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No


IR Quattro 8m KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079390
E-Nr. 535934708

Illustrations

TECHNICAL DRAWINGS



113 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 8,00 m BEREICH	2,8 m OPTIMAL	8,00 m MAX
--------------------------	------------------	---------------

IR Quattro 8m KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079390

E-Nr. 535934708

Highlights



Optional remote controls



Smart Remote remote control optional



Optional guard cage

IR Quattro 8m KNX - in-ceiling installation

PRESENCE DETECTOR

EAN 4007841079390
E-Nr. 535934708

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841593018	Service Fernbedienung RC6 KNX	Other
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory
 4007841592912	Nutzer Fernbedienung RC7 KNX	Accessory

ORDERING INFORMATION

Art.-Nr.

079390

EAN

4007841079390

E-Number

535934708

Typ

IR Quattro 8m KNX - in-ceiling installation

nevalux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss