

XLED PRO Wide SL weiss



Product code **4007841010232**

E-Nr. **924700270**

- Including STEINEL LED system
- Intelligent LED cooling system
- Optional basic lighting level
- UV resistant material
- Interconnectable by cable

neva
lux

165 x 265 x 126 mm



XLED PRO Wide SL weiss

Product code 4007841010232
E-Nr. 924700270

Technical Data

IDENTIFICATION					
Variant	white	LED colour deviation	SDCM3	Twilight setting	2 – 1000 lx
DIMENSIONS		Colour rendering index	80-89	Time setting	5 sec – 20 min
Dimensions L x W x H	165 x 265 x 126 mm	With illuminant	Yes, STEINEL LED system	Base light function time	10 min, 30 min, all night
ELECTRICAL		Illuminant	LED cannot be replaced	HOUSING & MATERIAL	
Mains connection	220 – 240 V , 50 / 60 Hz	LED cooling system	Passive Thermo Control	Impact resistance	IK00
Power	24,8 W	Continuous light	selectable, 4h	Protection class (IP)	IP54
SENSOR TECHNOLOGY		Luminous flux	2400 lm	Protection class	I
Max. mounting height	6,00 m	LIFETIME		Ambient temperature	-20 – 40 °C
With motion detector	No	LED lifetime max. °C	50000 h	Housing material	Aluminium
LIGHTING TECHNOLOGY		Luminous flux decline per LM80	L70B10	Cover material	Plastic, transparent
Colour temperature	4000 K	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
		Twilight switch	No	Manufacturer warranty	5 years

XLED PRO Wide SL weiss

Product code **4007841010232**
E-Nr. **924700270**

Illustrations

MOUNTING HEIGHT



XLED PRO Wide SL weiss

Product code **4007841010232**
E-Nr. **924700270**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841007638	Fernbedienung RC9	Other

ORDERING INFORMATION

Art.-Nr.

4007841010232

E-Number

924700270

Typ

XLED PRO Wide SL weiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss