

Single US LiveLink

neva
lux

Product code 4007841008437

- Optional surface-mounting adapter
- Optional guard cage

neva
lux

120 x 120 x 73 mm



Single US LiveLink

Product code 4007841008437

Technical Data

IDENTIFICATION					
Variant	LiveLink	Electronic scalability	Yes	Settings via	LiveLink app
Version	Presence detector	Mechanical scalability	No	Twilight setting teach	Yes
Model	LiveLink	Radial range	10 x 3 m (30 m²)	HOUSING & MATERIAL	
DIMENSIONS		Tangential range	10 x 3 m (30 m²)	Protection class (IP)	IP20
Dimensions L x W x H	120 x 120 x 73 mm	Mounting height	2,50 – 3,50 m	Mounting location	ceiling
ELECTRICAL		US technology	40 kHz	Application location	Indoors
Supply voltage detail	DALI bus	Optimal mounting height	2,8 m	Mounting type	Concealed wiring
Livelink values	Light level, Motion detection	CONNECTIVITY		Material	Plastic
SENSOR TECHNOLOGY		Networking	Yes	Colour	white
Sensor technology	Ultrasonic	Number of DALI participants	8	RAL colour	9010
Detection angle	180 °	With bus coupler	Yes	SCOPE OF DELIVERY & WARRANTY	
Opening angle	180 °	SETTINGS		Manufacturer warranty	5 years
Sneak-under protection	Yes	Twilight setting	10 – 1000 lx	OTHER	
		Time setting	60 sec – 60 min	Application, location, room	corridor, aisle, stairwell

Single US LiveLink

Product code 4007841008437

Illustrations

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL
--------------------------	------------------

Single US LiveLink

Product code 4007841008437

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841000363	Aufputz-Adapter Control Pro IP54 weiss	Accessory
 4007841003036	Control PRO Schutzkorb	Accessory
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841008437

Typ

Single US LiveLink

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss