

zola C1500 3CCT 30-58W



Product code **221566**

- Wide range of use in garages, basements, adjoining rooms, etc.
- 3 light colors selectable (3000, 4000 or 5700 Kelvin)
- Quick and easy mounting with separate mounting base
- Rear and side cable entry possible
- Wide beam diffuser (120 °)
- Version "Low Output" suitable for emergency lighting installations thanks to DC detection
- Available as emergency light version on request

neva
lux

1503 x 71 x 64 mm



zola C1500 3CCT 30-58W

Product code 221566

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions L x W x H	1503 x 71 x 64 mm	Colour rendering index	80-89	Impact resistance	IK08
ELECTRICAL		Illuminant	LED	Protection class (IP)	IP20
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	3600 lm (Default) / 4800 / 5760 / 6960 lm	Protection class	I
Power	30 W (Default) / 40 W / 48 W / 58 W	Beam angle	120°	Ambient temperature	-20...45 °C
Replaceable driver	Yes	Luminaire luminous efficacy	120 lm/W	Housing material	Steel
Type of wiring	Suitable for through wiring	LIFETIME		Cover material	Diffusor opal
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Mounting type	Ceiling / wall surface-mounted
With motion detector	No	SETTINGS		Colour	white
With light sensor	No	DALI dimming	No	SCOPE OF DELIVERY & WARRANTY	
LIGHTING TECHNOLOGY		With emergency light	No	Manufacturer warranty	5 years
Colour temperature	3000 / 4000 / 5700 K	Suitable for light band configuration	Yes	CERTIFICATES & EPREL	
LED colour deviation	SDCM3			EPREL energy efficiency class	E

zola C1500 3CCT 30-58W

Product code 221566

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 221410	zola P-Set	Suspension cable

ORDERING INFORMATION

Art.-Nr.

221566

Typ

zola C1500 3CCT 30-58W

neva
lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss