IS 240 DUO white

MOTION DETECTOR

EAN 4007841602819
E-Nr. 535997000

- Infrared motion detector with 240° detection angle and up to 12 m detection range
- For wall or corner mounting (incl. corner wall bracket) indoors and outdoors (IP 54), for reliable and uninterrupted surveillance of an area in front of two house walls
- Simple and flat design, made of UV-resistant plastic for a long service life
- Sensor can be swivelled horizontally by 160°, incl. cover plates for exact adjustment of the detection area
- Stepless adjustment of time (10 sec. - 15 min.) and switch-on brightness (2-2000 lux)
- Reliably switches any light source with a total of max. 1000 W switching load (LED light sources max. 350 W / 50 pcs.)
- Incl. mounting accessories - plastic-free packaging

100 x 60 x 90 mm



IS 240 DUO white

MOTION DETECTOR

EAN **4007841602819**
E-Nr. **535997000**

Technical Data

IDENTIFICATION

Version	**Motion detectors**

DIMENSIONS

Dimensions L × W × H	**100 x 60 x 90 mm**

ELECTRICAL

Mains connection	**230 V / 50 Hz**
Power	**1000 W**
Switching output 1 resistive	**1000 W**
Fluorescent lamps ECG	**350 W**
Fluorescent lamps uncompensated	**500 VA**
Fluorescent lamps series-compensated	**500 VA**
Fluorescent lamps parallel-compensated	**5000 VA**
Switching output 1 low-voltage halogen lamps	**1000 VA**
LED lamps < 2 W	**100 W**
LED lamps > 2 W < 8 W	**175 W**
LED lamps > 8 W	**350 W**
Capacitive load in µF	**132 µF**

SENSOR TECHNOLOGY

Max. mounting height	**4,00 m**
Sensor technology	**passive infrared**
Detection angle	**240 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Radial range	**r = 5 m (52 m²)**
Tangential range	**r = 12 m (302 m²)**
Switching zones	**276 switching zones**
Mounting height	**1,80 – 4,00 m**
Optimal mounting height	**2 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**2 – 2000 lx**
Time setting	**10 s – 15 Min.**
Base light function	**No**
Main light adjustable	**No**
Settings via	**Potentiometers**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP54**
Protection class	**II**
Ambient temperature	**from -20 up to 50 °C**
Mounting location	**corner wall**
Application location	**Indoors Outdoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Application room	**all round the building courtyard & driveway front door outdoors terrace / balcony**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**3 years**
Corner wall bracket included	**Yes**


IS 240 DUO white

MOTION DETECTOR

EAN **4007841602819**
E-Nr. **535997000**

Illustrations

TECHNICAL DRAWINGS



100 x 60 x 90 mm

MOUNTING HEIGHT

1,80 – 4,00 m	2 m	4,00 m
BEREICH	OPTIMAL	MAX


IS 240 DUO white

MOTION DETECTOR

EAN **4007841602819**
E-Nr. **535997000**


Wiring Diagrams

WIRING DIAGRAM 1



Light without neutral conductor

WIRING DIAGRAM 2



Light with neutral conductor

IS 240 DUO white

MOTION DETECTOR

EAN 4007841602819
E-Nr. 535997000

Highlights



UV-resistant plastic



Including corner wall mount

IS 240 DUO white

MOTION DETECTOR

EAN **4007841602819**
E-Nr. **535997000**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841630218	**Eckwandhalter 01 weiss**	Accessory

ORDERING INFORMATION

Art.-Nr.	602819
EAN	4007841602819
E-Number	535997000
Typ	**IS 240 DUO white**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss