

L 625 LED Alu silber

neva
lux

Product code **4007841053147**

- Including STEINEL LED system
- Intelligent soft light start
- Optional basic lighting level 25 %
- Including sheet of self-adhesive house numbers
- Sensor with 4 intelligent programmes
- High-quality aluminium
- UV resistant material

neva
lux

122 x 232 x 269 mm



L 625 LED Alu silber

Product code 4007841053147

Technical Data

IDENTIFICATION					
Variant	aluminium silver	Opening angle	90 °	Luminous flux	655 lm
DIMENSIONS		Sneak-under protection	Yes	LIFETIME	
Dimensions L x W x H	122 x 232 x 269 mm	Tangential range	r = 7 m (154 m²)	LED lifetime max. °C	50000 h
ELECTRICAL		LIGHTING TECHNOLOGY		SETTINGS	
Mains connection	220 – 240 V , 50 / 60 Hz	Efficiency	65 lm/W	Twilight setting	2 – 1000 lx
Power	10 W	Colour temperature	3000 K	Time setting	5 sec – 15 min
SENSOR TECHNOLOGY		LED colour deviation	SDCM3	HOUSING & MATERIAL	
Sensor technology	passive infrared	Colour rendering index	80-89	Protection class (IP)	IP44
Detection angle	360 °	Soft light start	Yes	Protection class	I
		Continuous light	selectable, 4h	Ambient temperature	-20 – 50 °C

L 625 LED Alu silber

Product code 4007841053147

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841006310	LED Ersatzpanel für L 270 / L 625 / L 665	Spare Part
 4007841006365	Ersatzglas für L 270 / L 625 / L 626	
 4007841009038	Ersatz-Minisensor silber	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841053147

Typ

L 625 LED Alu silber

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss