PD IR 4360-8 KNX - in-ceiling installation black

MOTION AND PRESENCE DETECTOR

EAN 4007841086183
E-Nr. 535900052

- Our series for the common ranges
- Presence detector with 8 m motion detection and 6 m presence detection for integration into a KNX bus system
- Ideal for offices, meeting rooms or passageways
- Includes insertable cover caps to limit the detection range
- Installation-friendly, thanks to round design and modular system with magnetic plug-in connection
- Start of programming mode from a distance via Smart Remote remote control via app
- External approval and measurement in accordance with sensNORM

109 x 109 mm



PD IR 4360-8 KNX - in-ceiling installation black

MOTION AND PRESENCE DETECTOR

EAN 4007841086183
E-Nr. 535900052

Technical Data

IDENTIFICATION

Version	Motion and Presence Detector

DIMENSIONS

Dimensions L × W × H	109 x 109 x 109 mm
Dimensions Ø × H	109 x 109 mm

SENSOR TECHNOLOGY

Max. mounting height	4,00 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	Ø 4.5 m (16 m²)
Tangential range	Ø 8 m (50 m²)
Switching zones	492 switching zones
Mounting height	2 – 4 m
Presence range	Ø 6 m (28 m²)
Optimal mounting height	2,8 m

CONNECTIVITY

Type of networking	Master/master
KNX functions	Light level Light output 2x Constant-lighting control Photo-cell controller Basic light level function HVAC output Logic gate Presence output Sabotage protection Day / night function
With bus coupler	Yes
Networking via	KNX

SETTINGS

Twilight setting	2 – 800 lx
Time setting	10 s – 1092 Min.
Functions	Motions sensor Light sensor Presence function Presence detector logic
Settings via	Smart Remote ETS software Bus
With remote control	No
Twilight setting teach	Yes

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Housing material	Plastic
Cover material	Other
Cover material (scope of delivery)	shrouds
Mounting location	ceiling
Application location	Indoors
Mounting type	In-ceiling installation
Material	Plastic
Application room	Indoors function room / ancillary room one-person office warehouse
Colour	black
RAL colour	9005

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No


PD IR 4360-8 KNX - in-ceiling installation black

MOTION AND PRESENCE DETECTOR

EAN **4007841086183**
E-Nr. **535900052**

Illustrations

TECHNICAL DRAWINGS



109 x 109 mm

MOUNTING HEIGHT

2 – 4 m	2,8 m	4,00 m
BEREICH	OPTIMAL	MAX

PD IR 4360-8 KNX - in-ceiling installation black

MOTION AND PRESENCE DETECTOR

EAN 4007841086183
E-Nr. 535900052

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841079543	**Deckeneinbau-Adapter Deckeneinbau**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841592806	**Nutzer Fernbedienung RC5**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	086183
EAN	4007841086183
E-Number	535900052
Typ	**PD IR 4360-8 KNX - in-ceiling installation black**

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss