DualTech COM1 - Concealed wiring

PRESENCE DETECTOR

EAN 4007841007997
E-Nr. 535931210

steinel

66 x 120 x 120 mm



DualTech COM1 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841007997**
E-Nr. **535931210**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**66 x 120 x 120 mm**

ELECTRICAL

Mains connection	**220 – 240 V / 50 – 60 Hz**
Power	**2000 W**
Fluorescent lamps ECG	**1500 W**
Fluorescent lamps uncompensated	**1000 VA**
Fluorescent lamps series-compensated	**1000 VA**
Fluorescent lamps parallel-compensated	**1000 VA**
Switching output 1 low-voltage halogen lamps	**2000 VA**
LED lamps < 2 W	**100 W**
LED lamps > 2 W < 8 W	**300 W**
LED lamps > 8 W	**600 W**
Capacitive load in µF	**176 µF**

SENSOR TECHNOLOGY

Max. mounting height	**3,50 m**
Sensor technology	**Ultrasonic**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**No**
Electronic scalability	**Yes**
Mechanical scalability	**No**

Radial range	**Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m²)**
Tangential range	**Ultrasonic: Ultraschall: Ø 10 m (Ultraschall: 79 m²)**
Switching zones	**520 switching zones**
Mounting height	**2,50 – 3,50 m**
Presence range	**Ultrasonic: Ultraschall: Ø 6 m (Ultraschall: 28 m²)**
Sensor technology 2	**passive infrared**
Radial range 2	**passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m²)**
Tangential range 2	**passive infrared: Passiv Infrarot: Ø 8 m (Passiv Infrarot: 50 m²)**
Presence range 2	**passive infrared: Passiv Infrarot: Ø 4 m (Passiv Infrarot: 13 m²)**
US technology	**40 kHz**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Type of networking	**Master/master Master/slave**
Networking quantity	**max. 10 sensors**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Soft light start	**No**
Continuous light	**selectable**
Constant light regulation	**No**

SETTINGS

Twilight switch	**Yes**
Twilight setting	**10 – 1000 lx**
Time setting	**30 s – 30 Min.**
Base light function	**No**
Main light adjustable	**No**
Functions	**Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF**
Settings via	**Remote control DIP switches Potentiometers Smart Remote**
With remote control	**No**
Twilight setting teach	**Yes**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**from -25 up to 55 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Concealed wiring**
Material	**Plastic**
Application room	**Indoors classroom conference room / meeting room duty room one-person office open-plan office recreation room**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**
Corner wall bracket included	**No**


DualTech COM1 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841007997**
E-Nr. **535931210**

Illustrations

TECHNICAL DRAWINGS



66 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,50 m	2,8 m	3,50 m
BEREICH	OPTIMAL	MAX


DualTech COM1 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841007997**
E-Nr. **535931210**


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

DualTech COM1 - Concealed wiring


PRESENCE DETECTOR

EAN 4007841007997
E-Nr. 535931210


Highlights



Optional remote controls



Optional surface-mounting adapter



Optional guard cage

DualTech COM1 - Concealed wiring

PRESENCE DETECTOR

EAN **4007841007997**
E-Nr. **535931210**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841009151	**Smart Remote**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	007997
EAN	4007841007997
E-Number	535931210
Typ	**DualTech COM1 - Concealed wiring**

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss