

IS 345 MX Highbay DALI-2 Input Device - UP eckig

neva
lux

Product code 4007841057404

E-Nr. 535942005

neva
lux

95 x 95 x 78 mm



IS 345 MX Highbay DALI-2 Input Device - UP eckig

Product code 4007841057404
E-Nr. 535942005

Technical Data

IDENTIFICATION		Mechanical scalability		No	With remote control		No
Variant	DALI-2 IPD - concealed, sq.	Radial range	12 x 6 m (72 m²)		Twilight setting teach		Yes
Version	Motion detectors	Tangential range	23 x 6 m (138 m²)		HOUSING & MATERIAL		
DIMENSIONS		Switching zones	280 switching zones		Protection class (IP)		IP20
Dimensions L x W x H	95 x 95 x 78 mm	Mounting height	4,00 – 14,00 m		Ambient temperature		-20 – 50 °C
ELECTRICAL		Optimal mounting height	12 m		Mounting location		ceiling
Mains connection	12 – 22,5 V / 50 – 60 Hz	CONNECTIVITY			Application location		Indoors
Control output DALI	Addressable/slave	Networking	Yes		Mounting type		Concealed wiring
SENSOR TECHNOLOGY		With bus coupler	Yes		Material		Plastic
Sensor technology	passive infrared	LIGHTING TECHNOLOGY			Colour		white
Detection angle	360 °	Constant light regulation	No		RAL colour		9003
Opening angle	45 °	SETTINGS			SCOPE OF DELIVERY & WARRANTY		
Sneak-under protection	Yes	Twilight setting	2 – 1000 lx		Manufacturer warranty		5 years
Segment-by-segment masking	Yes	Time setting	1 s – 60 Min.		OTHER		
Electronic scalability	No	Base light function	Yes		Application, location, room		high-bay warehouse
		Base light function time	1-30 min, all night				

IS 345 MX Highbay DALI-2 Input Device - UP eckig

Product code **4007841057404**
E-Nr. **535942005**

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL
---------------------------	-----------------

IS 345 MX Highbay DALI-2 Input Device - UP eckig

Product code **4007841057404**E-Nr. **535942005**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841057404

E-Number 535942005

Typ **IS 345 MX Highbay DALI-2 Input Device - UP eckig****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss