

fayola 125 DALI 4K

FAYOLA 100-205

neva
lux

Product code 220185

- Multi-purpose use in commercial properties and in the hotel industry
- High quality finish
- Optimized heat management, long service life
- Wide beam diffuser (70 °)
- Very good glare control values (UGR<19)
- Available in 5 different sizes
- Dimmable DALI, LiveLink compatible
- Brightness On-Off version adjustable in 4 steps
- Driver included

neva
lux

155 x 111 mm



fayola 125 DALI 4K

FAYOLA 100-205

Product code 220185

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø × H	155 x 111 mm	LED colour deviation	SDCM3	Protection class (IP)	IP20
Drill hole	125 mm	Colour rendering index	80-89	Protection class	II
ELECTRICAL		Illuminant	LED	Ambient temperature	-20...40 °C
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	1400 lm	Housing material	Aluminum
Power	15 W	Beam angle	70°	Cover material	Diffusor opal
Replaceable driver	Yes	Luminaire luminous efficacy	93 lm/W	Mounting type	In-ceiling installation
Type of wiring	Ending	Glare value	UGR < 19	Colour	white
LED rated current	350 mA	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
With motion detector	No	SETTINGS		CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		DALI dimming	Yes	EPREL energy efficiency class	F
Colour temperature	4000 K				

fayola 125 DALI 4K

FAYOLA 100-205

Product code 220185

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220184	fayola 100 DALI 4K	
 220186	fayola 150 DALI 4K	
 220187	fayola 175 DALI 4K	
 220188	fayola 205 DALI 4K	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220185

Typ

fayola 125 DALI 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss