

nyota C400 4K 120

neva
lux

Product code **221584**

- The powerful high-bay luminaire nevalux nyota is designed for the illumination of rooms with high ceilings. With its 32,000 lumens, this luminaire is the ideal choice for all types of industrial, exhibition and logistics halls. Thanks to the DALI driver integrated as standard, the light intensity can be ideally adapted to the respective conditions. The IP65 water jet protection combined with the IK09 shock resistance rating make this luminaire almost indestructible.

neva
lux

400 x 137 mm



nyota C400 4K 120

Product code 221584

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø × H	400 x 137 mm	LED colour deviation	SDCM3	Impact resistance	IK09
ELECTRICAL		Colour rendering index	80-89	Protection class (IP)	IP65
Mains connection	200...240 V / 50 – 60 Hz	Illuminant	LED	Protection class	I
Power	200 W	Luminous flux	32000 lm	Ambient temperature	-20...50 °C
Replaceable driver	Yes	Beam angle	120°	Housing material	Steel
Maximum number of luminaires per circuit breaker	C10: 5x, C13: 6x, C16: 8x, C25: 12x, B10: 3x, B13: 4x, B16: 5x, B25: 7x	Luminaire luminous efficacy	160 lm/W	Cover material	Diffusor opal
SENSOR TECHNOLOGY		Glare value	UGR < 30	Mounting type	Ceiling / Wall / Pendant
With motion detector	No	LIFETIME		Colour	black
With light sensor	No	LED lifespan (25 °C)	50000 h	SCOPE OF DELIVERY & WARRANTY	
LIGHTING TECHNOLOGY		SETTINGS		Manufacturer warranty	5 years
Colour temperature	4000 K	DALI dimming	Yes	CERTIFICATES & EPREL	
		With emergency light	No	EPREL energy efficiency class	C

nyota C400 4K 120

Product code **221584**

Accessories

ORDERING INFORMATION

Art.-Nr. 221584

Typ nyota C400 4K 120



nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss