# ayana connect LS C440 TW

**CEILING LUMINAIRE CONNECT**

Product code **222006**

- Timeless simple acrylic glass luminaire in 3 different sizes
- Available in ceiling and pendant versions
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- Connect version available with light sensor (LS) or with motion detector and light sensor (PIR)
- For universal use for illumination of offices, schools, traffic zones, etc.
- Very high quality workmanship from Swiss manufacturing
- Sophisticated thermal management for long service life
- Variants with adjustable light color (Tunable White) to emulate the natural course of daylight

440 x 95 mm



# ayana connect LS C440 TW

**CEILING LUMINAIRE CONNECT**

Product code **222006**

## Technical Data

### DIMENSIONS

| | |
|---|---|
| Dimensions Ø × H | **440 x 95 mm** |

### ELECTRICAL

| | |
|---|---|
| Mains connection | **200…240 V / 50 – 60 Hz** |
| Power | **43 W** |
| Replaceable driver | **Yes** |
| Type of wiring | **Suitable for through wiring** |

### SENSOR TECHNOLOGY

| | |
|---|---|
| With motion detector | **No** |
| With light sensor | **Yes** |

### CONNECTIVITY

| | |
|---|---|
| With radio network control | **Yes** |
| Control technology | **Smartlink Connect** |
| Wireless networking via | **BT SIG Mesh** |

### LIGHTING TECHNOLOGY

| | |
|---|---|
| Colour temperature | **3000…5600 K** |
| LED colour deviation | **SDCM3** |
| Colour rendering index | **80-89** |
| Illuminant | **LED** |
| Luminous flux | **5200 lm (Down 4470, Up 730)** |
| Beam angle | **105°** |
| Luminaire luminous efficacy | **122 lm/W** |
| Glare value | **UGR < 22** |

### LIFETIME

| | |
|---|---|
| LED lifespan (25 °C) | **70000 h** |

### SETTINGS

| | |
|---|---|
| DALI dimming | **Yes** |
| With emergency light | **No** |
| Direct/indirect ratio separately controllable | **No** |
| With program-controlled lighting control | **Yes** |

### HOUSING & MATERIAL

| | |
|---|---|
| Protection class (IP) | **IP20** |
| Protection class | **I** |
| Ambient temperature | **-20…45 °C** |
| Housing material | **Steel** |
| Cover material | **Acrylic glass opal** |
| Mounting type | **Ceiling / wall surface-mounted** |
| Colour | **white** |

### SCOPE OF DELIVERY & WARRANTY

| | |
|---|---|
| Manufacturer warranty | **5 years** |

### CERTIFICATES & EPREL

| | |
|---|---|
| EPREL energy efficiency class | **E** |


# ayana connect LS C440 TW

**CEILING LUMINAIRE CONNECT**

Product code **222006**

## Illustrations

### TECHNICAL DRAWINGS




440 x 95 mm


# ayana connect LS C440 TW

**CEILING LUMINAIRE CONNECT**

Product code **222006**


## Wiring Diagrams

**WIRING DIAGRAM 1**




Wiring diagram networking radio

**WIRING DIAGRAM 2**




Wiring diagram pushbutton coupler

# ayana connect LS C440 TW

**CEILING LUMINAIRE CONNECT**

Product code **222006**

## Accessories

| | ARTICLE NUMBER | DESCRIPTION | CATEGORY |
|---|---|---|---|
|   | 221103 | **ayana Diffusor 440 CDP** | Microprismatic Diffuser Ø440mm |
|  | 221108 | **Emergency Package 1h (Astra)** | Self-contained emergency lighting with self-test function |
|   | 221570 | **Connect TK2 BLM** | Pushbutton interface 2gang |
|  | 221591 | **Smartlink T-Board PB4** | Mobile push-button board |
|  | 221970 | **Bluetooth EDIZIO.liv SNAPFIX Low Energy PB2** | Wireless push-button, battery-free |
|  | 221971 | **Bluetooth EDIZIO.liv SNAPFIX Low Energy PB4** | Wireless push-button, battery-free |

**ORDERING INFORMATION**

| | |
|---|---|
| Art.-Nr. | 222006 |
| Typ | **ayana connect LS C440 TW** |

neva lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss