HF 360 DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002817
E-Nr. 535934504

steinel

56 x 120 x 120 mm



HF 360 DALI-2 APC - concealed

PRESENCE DETECTOR

EAN 4007841002817
E-Nr. 535934504

Technical Data

IDENTIFICATION

Version	Presence detector

DIMENSIONS

Dimensions L × W × H	56 x 120 x 120 mm

ELECTRICAL

Mains connection	230 V / 50 – 60 Hz
Control output DALI	Broadcast 2x12 electronic ballasts

SENSOR TECHNOLOGY

Max. mounting height	3,50 m
Sensor technology	High frequency
Transmission power	< 1 mW
HF technology	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	140 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Range detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
Radial range	Ø 12 m (113 m²)
Tangential range	Ø 12 m (113 m²)
Mounting height	2,50 – 3,50 m
Optimal mounting height	2,8 m

CONNECTIVITY

Networking	Yes
Type of networking	Master/slave
With bus coupler	Yes
Networking via	DALI 2

LIGHTING TECHNOLOGY

Soft light start	Yes
Continuous light	selectable
Constant light regulation	Yes

SETTINGS

Twilight switch	Yes
Twilight setting	10 – 1000 lx
Time setting	30 s – 30 Min.
Base light function	Yes
Base light function time	1-60 min, all night
Main light adjustable	50 - 100 %
Functions	Normal / test mode Semi-/fully automatic Pushbutton / switch mode Manual ON / ON-OFF Constant-lighting control ON-OFF
Settings via	Remote control DIP switches Potentiometers Smart Remote
With remote control	No
Twilight setting teach	Yes
Base light function in percent	10 – 60 %
Base light function percent from	10 %

HOUSING & MATERIAL

Protection class (IP)	IP20
Ambient temperature	from -25 up to 55 °C
Mounting location	ceiling
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors WC / washroom function room / ancillary room kitchenette stairwell
Colour	white
RAL colour	9010

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	5 years
Corner wall bracket included	No

CERTIFICATES & EPREL

Certificates	DALI-2


HF 360 DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841002817**
E-Nr. **535934504**

Illustrations

TECHNICAL DRAWINGS



56 x 120 x 120 mm

MOUNTING HEIGHT

2,50 – 3,50 m BEREICH	2,8 m OPTIMAL	3,50 m MAX


HF 360 DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841002817**
E-Nr. **535934504**


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/master interconnection circuit diagram

HF 360 DALI-2 APC - concealed


PRESENCE DETECTOR

EAN **4007841002817**
E-Nr. **535934504**


Highlights



Optional remote control



Optional surface-mounting adapter



Optional guard cage



HF ceiling adapter for installation in suspended ceilings

HF 360 DALI-2 APC - concealed

PRESENCE DETECTOR

EAN **4007841002817**
E-Nr. **535934504**

Accessories

	ARTICLE NUMBER	DESCRIPTION	CATEGORY
	4007841006600	**HF-Deckenadapter**	Accessory
	4007841592806	**Nutzer Fernbedienung RC5**	Accessory
	4007841009151	**Smart Remote**	Accessory
	4007841000363	**Aufputz-Adapter Control Pro IP54 weiss**	Accessory
	4007841003036	**Control PRO Schutzkorb**	Accessory
	4007841559410	**Service Fernbedienung RC8**	Accessory

ORDERING INFORMATION

Art.-Nr.	002817
EAN	4007841002817
E-Number	535934504
Typ	**HF 360 DALI-2 APC - concealed**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss