

RS PRO 5100 C ohne Bewegungsmelder

neva
lux

Product code **4007841079178**

E-Nr. **941336979**

- Including STEINEL LED system
- Interconnectable and adjustable via Bluetooth
- Impact-resistant material rated to IK07
- Optional basic lighting level 0 - 100 %
- Adjustable main light brightness (0 - 100%)
- Adjustable mounts for easy installation

neva
lux

1370 x 87 x 58 mm



RS PRO 5100 C ohne Bewegungsmelder

Product code **4007841079178**
E-Nr. **941336979**

Technical Data

DIMENSIONS		Colour temperature		4000 K	Protection class (IP)		IP65
Dimensions L x W x H		1370 x 87 x 58 mm			Protection class		II
ELECTRICAL		LED cooling system		Passive Thermo Control	Ambient temperature		-20 – 40 °C
Mains connection		220 – 240 V / 50 – 60 Hz			Housing material		Plastic
Power		31 W			Cover material		Plastic, structured
Own consumption		0,45 W			Mounting location		ceiling wall
SENSOR TECHNOLOGY		LIFETIME			Colour		grey
With motion detector		No			SCOPE OF DELIVERY & WARRANTY		
Electronic scalability		Yes			Manufacturer warranty		5 years
CONNECTIVITY		SETTINGS			CERTIFICATES & EPREL		
Networking via		Bluetooth Mesh Connect			Certificates		DEKRA
LIGHTING TECHNOLOGY		HOUSING & MATERIAL			EPREL category		Surrounded product with integrated light source
Measured luminous flux 360°		4250 lm			Impact resistance		IK07

RS PRO 5100 C ohne Bewegungsmelder

Product code **4007841079178**E-Nr. **941336979**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841079178

E-Number 941336979

Typ **RS PRO 5100 C ohne Bewegungsmelder****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss