

lisha P1200 4K

LISHA

neva
lux

Product code **220180**

- For universal use for lighting offices, schools, traffic zones, etc.
- Available as intelligent Connect version or as conventional DALI luminaire
- Connect variant with powerful IoT lighting control for next-generation lighting projects (swarm function, grouping, cleaning light, etc.)
- Direct and indirect light proportion separately controllable
- Link technology for seamless extension of the luminaire with continuous wiring
- Variants with 1.2 and 1.8 meter length available
- Housing Aluminium RAL9016, white

neva
lux

1205 x 50 x 95 mm



lisha P1200 4K

LISHA

Product code 220180

Technical Data

DIMENSIONS		LED colour deviation	SDCM3	Constant light output control	Yes
Dimensions L x W x H	1205 x 50 x 95 mm	Colour rendering index	80-89	HOUSING & MATERIAL	
Suspension length	1500 mm	Illuminant	LED	Protection class (IP)	IP20
ELECTRICAL		Luminous flux	5500 lm (Down 3800, Up 1700)	Protection class	I
Mains connection	200...240 V / 50 – 60 Hz	Beam angle	Down 105°, Up 115°	Ambient temperature	-20...45 °C
Power	49 W	Luminaire luminous efficacy	112 lm/W	Housing material	Aluminum
Replaceable driver	Yes	Glare value	UGR < 22	Cover material	Acrylic glass opal
Type of wiring	Through wiring included	LIFETIME		Mounting type	Ceiling pendant
LED rated current	700 mA / 250 mA	LED lifespan (25 °C)	50000 h	Colour	white
Maximum number of luminaires per circuit breaker	C10: 15x, C16: 23x, C20: 29x, B10: 9x, B16: 14x, B25: 17x	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		DALI dimming	Yes	Manufacturer warranty	5 years
With motion detector	No	With emergency light	No	CERTIFICATES & EPREL	
With light sensor	No	Suitable for light band configuration	Yes	EPREL energy efficiency class	E
LIGHTING TECHNOLOGY		Direct/indirect ratio separately controllable	Yes		
Colour temperature	4000 K				

lisha P1200 4K

LISHA

Product code **220180**

Accessories

ORDERING INFORMATION	
Art.-Nr.	220180
Typ	lisha P1200 4K
nevalux nevalux AG Neugrütstrasse 2 8610 Uster +41 44 508 78 78 info@nevalux.swiss	