BLS

PRESENCE DETECTOR

EAN 4007841720414
E-Nr. 924360109

- Multi-lens
- Shrouds

120 x 120 x 66 mm



BLS

PRESENCE DETECTOR

EAN **4007841720414**
E-Nr. **924360109**

Technical Data

IDENTIFICATION

Version	**Presence detector**

DIMENSIONS

Dimensions L × W × H	**120 x 120 x 66 mm**

ELECTRICAL

Mains connection	**230 – 240 V , 50 / 50 Hz**
Switching output 1 resistive	**2000 W**

SENSOR TECHNOLOGY

Sensor technology	**passive infrared**
Detection angle	**360 °**
Opening angle	**180 °**
Sneak-under protection	**Yes**
Segment-by-segment masking	**Yes**
Electronic scalability	**No**
Mechanical scalability	**No**
Tangential range	**Ø 24 m (452 m²)**
Switching zones	**1320 switching zones**
Mounting height	**2,50 – 3,00 m**
Presence range	**Ø 4 m (13 m²)**
Optimal mounting height	**2,8 m**

CONNECTIVITY

Networking	**Yes**
Control technology	**On/Off-Leuchte**

LIGHTING TECHNOLOGY

Constant light regulation	**No**

SETTINGS

Twilight setting	**20 – 1300 lx**
Time setting	**280 sec – 30 min**
Base light function	**No**
With remote control	**No**
Twilight setting teach	**No**

HOUSING & MATERIAL

Protection class (IP)	**IP20**
Ambient temperature	**-20 – 50 °C**
Mounting location	**ceiling**
Application location	**Indoors**
Mounting type	**Surface wiring**
Material	**Plastic**
Colour	**white**
RAL colour	**9010**

SCOPE OF DELIVERY & WARRANTY

Manufacturer warranty	**5 years**

BLS

PRESENCE DETECTOR

EAN **4007841720414**
E-Nr. **924360109**

Illustrations

MOUNTING HEIGHT

2,50 – 3,00 m BEREICH	2,8 m OPTIMAL

BLS

PRESENCE DETECTOR

EAN **4007841720414**
E-Nr. **924360109**

Accessories

ORDERING INFORMATION

Art.-Nr.	4007841720414
EAN	4007841720414
E-Number	924360109
Typ	**BLS**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss