

RS PRO P1 Neutral white

LED INDOOR LIGHT WITHOUT SENSOR

neva
lux

EAN 4007841056049

E-Nr. 941000169

 **steinel**

280 x 110 mm



RS PRO P1 Neutral white

LED INDOOR LIGHT WITHOUT SENSOR

EAN 4007841056049

E-Nr. 941000169

Technical Data

DIMENSIONS	
Dimensions Ø × H	280 x 110 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	8,2 W
SENSOR TECHNOLOGY	
With motion detector	No
CONNECTIVITY	
Networking via	Cable
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	974 lm
Colour temperature	4000 K

With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
LIFETIME	
LED lifetime max. °C	50000 h
LED lifetime L70B50 25°C	> 60000 h
Luminous flux decline per LM80	L80B10
SETTINGS	
Main light adjustable	No
HOUSING & MATERIAL	
Impact resistance	IK03

Protection class (IP)	IP54
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Mounting location	ceiling wall
Colour	white
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
CERTIFICATES & EPREL	
Certificates	DEKRA
EPREL category	Surrounded product with integrated light source

RS PRO P1 Neutral white


LED INDOOR LIGHT WITHOUT SENSOR

EAN 4007841056049

E-Nr. 941000169

Illustrations

TECHNICAL DRAWINGS



280 x 110 mm

RS PRO P1 Neutral white


LED INDOOR LIGHT WITHOUT SENSOR

EAN 4007841056049

E-Nr. 941000169


Wiring Diagrams

WIRING DIAGRAM 1



Master circuit diagram

WIRING DIAGRAM 2



Master/slave interconnection circuit diagram

RS PRO P1 Neutral white

LED INDOOR LIGHT WITHOUT SENSOR


EAN 4007841056049

E-Nr. 941000169

Highlights



Including STEINEL LED system



Intelligent soft light start



Interconnectable by cable (maximum of 10 units)

RS PRO P1 Neutral white

LED INDOOR LIGHT WITHOUT SENSOR

EAN **4007841056049**
E-Nr. **941000169**

Accessories

ORDERING INFORMATION

Art.-Nr.	056049
EAN	4007841056049
E-Number	941000169
Typ	RS PRO P1 Neutral white

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss