

zwena DALI P900 4K

ZWENA CONNECT P

neva
lux

Product code **220584**

- For universal use for illumination of offices, schools, traffic zones, etc.
- Optionally as an intelligent Connect version with or without motion sensor, or as a conventional DALI luminaire
- Connect version with IoT lighting control for next generation lighting projects (swarm function, grouping, cleaning light etc.)
- High quality finish
- Direct and indirect light distribution

neva
lux

900 x 82 mm



zwena DALI P900 4K

ZWENA CONNECT P

Product code 220584

Technical Data

DIMENSIONS					
Dimensions Ø x H	900 x 82 mm	LED colour deviation	SDCM3	Direct/indirect ratio separately controllable	No
Suspension length	1500 mm	Colour rendering index	80-89	HOUSING & MATERIAL	
ELECTRICAL		Illuminant	LED	Protection class (IP)	IP20
Mains connection	200...240 V / 50 – 60 Hz	Luminous flux	9000 lm (Down 5600, Up 3400)	Protection class	I
Power	80 W	Beam angle	Down 95°, Up 100°	Ambient temperature	-20...45 °C
Replaceable driver	Yes	Luminaire luminous efficacy	113 lm/W	Housing material	Aluminum
Type of wiring	Suitable for through wiring	Glare value	UGR < 18	Cover material	Microprismatic acrylic glass
LED rated current	2100 mA	LIFETIME		Mounting type	Ceiling pendant
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Colour	white
With motion detector	No	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
With light sensor	No	DALI dimming	Yes	Manufacturer warranty	5 years
LIGHTING TECHNOLOGY		With emergency light	No	CERTIFICATES & EPREL	
Colour temperature	4000 K			EPREL energy efficiency class	E

zwena DALI P900 4K

Product code 220584

ZWENA CONNECT P

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220578	zwena DALI P350 4K	
 220580	zwena DALI P450 4K	
 220582	zwena DALI P600 4K	
 221618	Emergency Package 1h (50V/3.5W)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.220584

Typzwena DALI P900 4K

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss