

IS 345 MX Highbay LiveLink - Aufputz eckig

neva
lux

Product code 4007841009731

E-Nr. 535941030

neva
lux

95 x 95 x 65 mm



IS 345 MX Highbay LiveLink - Aufputz eckig

Product code **4007841009731**
E-Nr. **535941030**

Technical Data

IDENTIFICATION					
Variant	LiveLink - surface-mounted, square	Segment-by-segment masking	Yes	Base light function	No
Version	Motion detectors	Electronic scalability	No	Settings via	LiveLink app
Model	LiveLink	Mechanical scalability	No	With remote control	No
DIMENSIONS		Radial range	30 x 4 m (120 m²)	Twilight setting teach	Yes
Dimensions L x W x H	95 x 95 x 65 mm	Tangential range	30 x 4 m (120 m²)	HOUSING & MATERIAL	
ELECTRICAL		Switching zones	280 switching zones	Protection class (IP)	IP54
Mains connection	16 V	Mounting height	4,00 – 14,00 m	Ambient temperature	-20 – 50 °C
Supply voltage detail	DALI bus	Optimal mounting height	12 m	Mounting location	ceiling
Livelihood values	Light level, Motion detection, Presence detection	CONNECTIVITY		Application location	Indoors
SENSOR TECHNOLOGY		Networking	Yes	Mounting type	Surface wiring
Sensor technology	passive infrared	Number of DALI participants	3	Material	Plastic
Detection angle	360 °	LIGHTING TECHNOLOGY		Colour	white
Opening angle	9 °	Constant light regulation	Yes	RAL colour	9003
Sneak-under protection	Yes	SETTINGS		SCOPE OF DELIVERY & WARRANTY	
		Twilight setting	2 – 1000 lx	Manufacturer warranty	5 years
		Time setting	60 sec – 60 min	OTHER	
				Application, location, room	high-bay warehouse

IS 345 MX Highbay LiveLink - Aufputz eckig

Product code 4007841009731
E-Nr. 535941030

Illustrations

MOUNTING HEIGHT

4,00 – 14,00 m BEREICH	12 m OPTIMAL
---------------------------	-----------------

IS 345 MX Highbay LiveLink - Aufputz eckig

Product code **4007841009731**E-Nr. **535941030**

Accessories

ORDERING INFORMATION

Art.-Nr. 4007841009731

E-Number 535941030

Typ **IS 345 MX Highbay LiveLink - Aufputz eckig****neva
lux**

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss