

sensIQ weiss

neva
lux

Product code 4007841020439

- 4x pyro system
- Suitable for mounting on ceilings
- UV-resistant plastic
- Wireless interconnection
- Including corner wall mount
- Smart Remote remote control optional
- Remote control RC9 included

neva
lux

172 x 113 x 144 mm



Technical Data

IDENTIFICATION			
Version	Motion detectors	Detection angle	300 °
Type of accessory	Corner adapter	Opening angle	180 °
DIMENSIONS		Sneak-under protection	Yes
Dimensions L × W × H	172 x 113 x 144 mm	Segment-by-segment masking	Yes
ELECTRICAL		Electronic scalability	No
Mains connection	220 – 240 V / 50 – 60 Hz	Mechanical scalability	Yes
Power	2500 W	Range detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Fluorescent lamps ECG	1500 W	Radial range	r = 4 m (42 m²)
Fluorescent lamps uncompensated	1000 VA	Tangential range	r = 20 m (1047 m²)
Fluorescent lamps series-compensated	1800 VA	Switching zones	1360 switching zones
Fluorescent lamps parallel-compensated	500 VA	Mounting height	2,00 – 5,00 m
Switching output 1 low-voltage halogen lamps	2300 VA	Optimal mounting height	2 m
SENSOR TECHNOLOGY		CONNECTIVITY	
Max. mounting height	5,00 m	Networking	Yes
Sensor technology	passive infrared	Networking via	Wireless
With motion detector	Yes	LIGHTING TECHNOLOGY	
		Soft light start	No
		Continuous light	selectable, 4h
		Constant light regulation	No
		SETTINGS	
		Twilight switch	Yes
		Twilight setting	2 – 2000 lx
		Time setting	5 sec – 15 min

Base light function	No
Main light adjustable	No
Functions	Connection to eNet server\nPush button configuration
Settings via	Remote control\nPotentiometers\neNet
With remote control	Yes
Twilight setting teach	Yes
HOUSING & MATERIAL	
Ambient temperature	-20 – 50 °C
Mounting location	ceiling corner wall
Application location	Indoors Outdoors
Mounting type	Surface wiring
Material	Plastic
Application room	Indoors all round the building courtyard & driveway front door multi-storey / underground car park outdoors warehouse
Colour	white
RAL colour	9010
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	Yes
CERTIFICATES & EPREL	
Certificates	VDE

sensIQ weiss

Product code 4007841020439

Illustrations

MOUNTING HEIGHT

2,00 – 5,00 m BEREICH	2 m OPTIMAL	5,00 m MAX
--------------------------	----------------	---------------

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009151	Smart Remote	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841020439

Typ

sensIQ weiss

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss