

HF 3360 COM1 - Unterputz rund

neva
lux

Product code 4007841033682

E-Nr. 535940760

- UV-resistant plastic
- Optional remote controls

neva
lux

124 x 64 mm



HF 3360 COM1 - Unterputz rund

Product code **4007841033682**

E-Nr. **535940760**

Technical Data

IDENTIFICATION	
Version	Motion detectors
DIMENSIONS	
Dimensions Ø × H	124 x 64 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	2000 W
Switching output 1 resistive	2000 W
Fluorescent lamps ECG	1500 W
Fluorescent lamps uncompensated	1000 VA
Fluorescent lamps series-compensated	400 VA
Fluorescent lamps parallel-compensated	400 VA
Switching output 1 low-voltage halogen lamps	2000 VA
LED lamps < 2 W	100 W
LED lamps > 2 W < 8 W	300 W
LED lamps > 8 W	600 W
Capacitive load in µF	176 µF
Switching output 1 number of LED/fluorescent lamps	8 pcs.
SENSOR TECHNOLOGY	
Max. mounting height	4,00 m
Sensor technology	High frequency

Transmission power	< 1 mW
HF technology	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Opening angle	180 °
Sneak-under protection	Yes
Segment-by-segment masking	No
Electronic scalability	Yes
Mechanical scalability	No
Radial range	Ø 8 m (50 m²)
Tangential range	Ø 8 m (50 m²)
Mounting height	2,00 – 4,00 m
Optimal mounting height	2,8 m
CONNECTIVITY	
Networking	Yes
Type of networking	Master/master
Networking via	Cable
LIGHTING TECHNOLOGY	
Soft light start	No
Continuous light	selectable, 4h
Constant light regulation	No
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 1000 lx

Time setting	5 s – 15 Min.
Base light function	No
Main light adjustable	No
Functions	Normal / test mode\nManual ON / ON-OFF
Settings via	Remote control\nPotentiometers\nSmart Remote
With remote control	No
Twilight setting teach	Yes
HOUSING & MATERIAL	
Protection class (IP)	IP20
Ambient temperature	from -20 up to 50 °C
Mounting location	ceiling corner wall
Application location	Indoors
Mounting type	Concealed wiring
Material	Plastic
Application room	Indoors WC / washroom function room / ancillary room multi-storey / underground car park stairwell
Colour	white
RAL colour	9003
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
Corner wall bracket included	No

HF 3360 COM1 - Unterputz rund

Product code **4007841033682**
E-Nr. **535940760**

Illustrations

MOUNTING HEIGHT

2,00 – 4,00 m BEREICH	2,8 m OPTIMAL	4,00 m MAX
--------------------------	------------------	---------------

HF 3360 COM1 - Unterputz rund

Product code **4007841033682**
E-Nr. **535940760**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841056681	Schwarze Blende für den HF 3360 Unterputz eckig	Coverage
 4007841056704	Schwarze Blende für den HF 3360 Unterputz rund	Coverage
 4007841009151	Smart Remote	Accessory
 4007841559410	Service Fernbedienung RC8	Accessory

ORDERING INFORMATION

Art.-Nr.

4007841033682

E-Number

535940760

Typ

HF 3360 COM1 - Unterputz rund

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss