

fayola 175 On-Off 4K

FAYOLA 100-205

neva
lux

Product code 220435

- Multi-purpose use in commercial properties and in the hotel industry
- High quality finish
- Optimized heat management, long service life
- Wide beam diffuser (70 °)
- Very good glare control values (UGR<19)
- Available in 5 different sizes
- Dimmable DALI, LiveLink compatible
- Brightness On-Off version adjustable in 4 steps
- Driver included

neva
lux

200 x 136 mm



fayola 175 On-Off 4K

FAYOLA 100-205

Product code 220435

Technical Data

DIMENSIONS				HOUSING & MATERIAL	
Dimensions Ø x H	200 x 136 mm	LED colour deviation	SDCM3	Protection class (IP)	IP20
Drill hole	175 mm	Colour rendering index	80-89	Protection class	II
ELECTRICAL		Illuminant	LED	Ambient temperature	-20...40 °C
Mains connection	220...240 V / 50 – 60 Hz	Luminous flux	2000 lm	Housing material	Aluminum
Power	21 W	Beam angle	70°	Cover material	Diffusor opal
Replaceable driver	Yes	Luminaire luminous efficacy	95 lm/W	Mounting type	In-ceiling installation
Type of wiring	Ending	Glare value	UGR < 19	Colour	white
LED rated current	500 mA	LIFETIME		SCOPE OF DELIVERY & WARRANTY	
SENSOR TECHNOLOGY		LED lifespan (25 °C)	50000 h	Manufacturer warranty	5 years
With motion detector	No	SETTINGS		CERTIFICATES & EPREL	
LIGHTING TECHNOLOGY		DALI dimming	No	EPREL energy efficiency class	F
Colour temperature	4000 K				

fayola 175 On-Off 4K

FAYOLA 100-205

Product code 220435

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 220432	fayola 100 On-Off 4K	
 220433	fayola 125 On-Off 4K	
 220434	fayola 150 On-Off 4K	
 220436	fayola 205 On-Off 4K	
 220721	Emergency Package 1h (50V/2.5W/Box)	Emergency lighting

ORDERING INFORMATION

Art.-Nr.

220435

Typ

fayola 175 On-Off 4K

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss