

RS PRO DL LED 15 W Slave - warmweiss

neva
lux

Product code **4007841007737**

E-Nr. **941311109**

- Including STEINEL LED system
- Intelligent LED cooling system
- Ceiling-flush installation
- Interconnectable by cable ?(maximum of 10 units)
- Can only be set by optional remote control RC2

neva
lux

142.5 x 88 mm



RS PRO DL LED 15 W Slave - warmweiss

Product code **4007841007737**
E-Nr. **941311109**

Technical Data

IDENTIFICATION		LIGHTING TECHNOLOGY		SETTINGS	
Variant	Slave - warm white	Colour temperature	3000 K	Twilight switch	No
DIMENSIONS		LED colour deviation	SDCM3	Time setting	60 sec – 60 min
Dimensions Ø × H	142.5 x 88 mm	Colour rendering index	80-89	Base light function time	10 min, 30 min, all night
ELECTRICAL		With illuminant	Yes, STEINEL LED system	HOUSING & MATERIAL	
Mains connection	100 – 240 V , 50 / 60 Hz	Illuminant	LED cannot be replaced	Impact resistance	IK00
Power	15 W	Base	without	Protection class (IP)	IP20
Power detail	Only via Eltako ER12DX-UC with basic light function deactivated	LED cooling system	Passive Thermo Control	Protection class	II
SENSOR TECHNOLOGY		Luminous flux	707,4 lm	Ambient temperature	-10 – 40 °C
Transmission power	< 1 mW	LIFETIME		Housing material	Aluminium
With motion detector	No	LED lifetime max. °C	50000 h	Cover material	Plastic, opal
		Luminous flux decline per LM80	L70B10	SCOPE OF DELIVERY & WARRANTY	
				Manufacturer warranty	5 years

RS PRO DL LED 15 W Slave - warmweiss

Product code **4007841007737**
E-Nr. **941311109**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841737818	RS PRO Fernbedienung RC2	
 4007841009151	Smart Remote	Accessory
 4007841013677	Sanierungsblende für RS PRO DL LED 15 W	

ORDERING INFORMATION

Art.-Nr.

4007841007737

E-Number

941311109

Typ

RS PRO DL LED 15 W Slave - warmweiss

neva

lux

nevalux AG

Neugrütstrasse 2

8610 Uster

+41 44 508 78 78

info@nevalux.swiss