

L 270 digi SC with motion detector & Bluetooth

neva
lux

SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799

- Outdoor luminaire with motion detector and illuminated house number panel in flat linear design
- Invisibly integrated sensor with three individually adjustable detection areas
- Wireless networking via Bluetooth Mesh and easy setting via STEINEL Connect App
- Automatic light thanks to 180° infrared sensor with up to 8 m detection of movement (detection quality equally reliable regardless of walking direction)
- Functions: adjustable basic and main light, pleasant soft light start, continuous light, scheduling function
- Warm white light (3000 K) and long-life 7,8 W LEDs with 637 lm
- Incl. mounting accessories - plastic-free packaging

 **steinel**

65 x 366 x 235 mm



L 270 digi SC with motion detector & Bluetooth

SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799

Technical Data

DIMENSIONS	
Dimensions L x W x H	65 x 366 x 235 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	7,8 W
SENSOR TECHNOLOGY	
Max. mounting height	2,50 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	180 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	Yes
Mechanical scalability	No
Range detail	3 detection zones can be (de)activated individually, range can be set separately
Radial range	r = 6 m (57 m²)
Tangential range	r = 8 m (101 m²)
Mounting height	1,80 – 2,50 m
Optimal mounting height	2 m
CONNECTIVITY	
Networking	Yes
Networking via	Bluetooth Mesh

Slave mode adjustable	Yes
LIGHTING TECHNOLOGY	
Measured luminous flux 360°	637 lm
Efficiency	82 lm/W
Colour temperature	3000 K
Colour rendering index	= 82
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Soft light start	Yes
Continuous light	selectable
LIFETIME	
LED lifetime L70B50 25°C	> 60000 h
Average rated power supply lifetime at 25 °C	> 60000 h
SETTINGS	
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Base light function	Yes
Base light function detail	LED effect light
Base light function time	10s-60 min OFF Brightness-controlled
Main light adjustable	5 - 100 %
Settings via	App Smartphone Tablet Bluetooth Mesh
With remote control	No

Twilight setting teach	Yes
Base light function in percent	5 – 100 %
Base light function percent from	5 %
HOUSING & MATERIAL	
Impact resistance	IK03
Protection class (IP)	IP44
Protection class	II
Ambient temperature	from -10 up to 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Mounting location	wall
Application location	Outdoors
Mounting type	Surface wiring
Material	Aluminium
Application room	front door outdoors
Colour	Anthracite
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	3 years
House number sheet included	Yes
CERTIFICATES & EPREL	
EPREL category	Surrounded product with integrated light source

L 270 digi SC with motion detector & Bluetooth


SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799

Illustrations

TECHNICAL DRAWINGS



65 x 366 x 235 mm

MOUNTING HEIGHT

1,80 – 2,50 m BEREICH	2 m OPTIMAL	2,50 m MAX
--------------------------	----------------	---------------

L 270 digi SC with motion detector & Bluetooth


SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799

Wiring Diagrams

WIRING DIAGRAM 1



Circuit diagram Bluetooth


L 270 digi SC with motion detector & Bluetooth

SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799


Highlights



Intelligent soft light start



High-quality aluminium



Operatable via app



Interconnectable and adjustable via Bluetooth



Including sheet of self-adhesive house numbers



House number panel mountable on both sides

L 270 digi SC with motion detector & Bluetooth

SENSOR-SWITCHED LED OUTDOOR LIGHT

EAN 4007841067205

E-Nr. 941012799

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
4007841088620	Funkschalter TapDuo C	System components

ORDERING INFORMATION

Art.-Nr.

067205

EAN

4007841067205

E-Number

941012799

Typ

L 270 digi SC with motion detector & Bluetooth

nevalux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss