

L 665 S anthrazit

neva
lux

Product code **4007841053949**

E-Nr. **941200249**

- Including STEINEL LED system
- Intelligent soft light start
- Optional basic lighting level 10 %
- Sensor with 4 intelligent programmes
- High-quality aluminium
- Including sheet of self-adhesive house numbers
- Interconnectable by cable (K-line)
- Panel can be moved to the left or right

neva
lux

122 x 326 x 269 mm



L 665 S anthrazit

Product code **4007841053949**
E-Nr. **941200249**

Technical Data

DIMENSIONS	
Dimensions L x W x H	122 x 326 x 269 mm
ELECTRICAL	
Mains connection	220 – 240 V / 50 – 60 Hz
Power	10,4 W
Power detail	1 W LED house number illumination
SENSOR TECHNOLOGY	
Max. mounting height	2,50 m
Sensor technology	passive infrared
With motion detector	Yes
Detection angle	360 °
Sneak-under protection	Yes
Segment-by-segment masking	Yes
Electronic scalability	No
Mechanical scalability	No
Radial range	r = 2 m (13 m²)
Tangential range	r = 7 m (154 m²)
Mounting height	1,80 – 2,50 m
Optimal mounting height	2 m
CONNECTIVITY	
Networking	Yes
Networking via	Cable
Slave mode adjustable	No

LIGHTING TECHNOLOGY	
Measured luminous flux 360°	611 lm
Efficiency	59 lm/W
Colour temperature	3000 K
LED colour deviation	SDCM3
Colour rendering index	= 82
With illuminant	Yes, STEINEL LED system
Illuminant	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable, 4h
LIFETIME	
LED lifetime L70B50 25°C	> 60000 h
Average rated power supply lifetime at 25 °C	> 60000 h
SETTINGS	
Twilight switch	Yes
Twilight setting	2 – 1000 lx
Time setting	5 s – 15 Min.
Base light function	Yes
Base light function time	10/30 min, all night
Functions	4 programme settings geared to practical needs, can be selected on removable sensor module
Settings via	Potentiometers

With remote control	No
Base light function in percent	10 %
Base light function percent from	10 %
HOUSING & MATERIAL	
Impact resistance	IK07
Protection class (IP)	IP44
Protection class	I
Ambient temperature	-20 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Cover material (scope of delivery)	shrouds
Mounting location	wall
Application location	Outdoors
Mounting type	Surface wiring
Material	Aluminium
Application room	courtyard & driveway front door outdoors
Colour	Anthracite
SCOPE OF DELIVERY & WARRANTY	
Manufacturer warranty	5 years
House number sheet included	Yes
CERTIFICATES & EPREL	
EPREL category	Surrounded product with integrated light source

L 665 S anthrazit

Product code **4007841053949**
E-Nr. **941200249**

Illustrations

MOUNTING HEIGHT

1,80 – 2,50 m BEREICH	2 m OPTIMAL	2,50 m MAX
--------------------------	----------------	---------------

L 665 S anthrazit

Product code **4007841053949**
E-Nr. **941200249**

Accessories

ARTICLE NUMBER	DESCRIPTION	CATEGORY
 4007841009014	Ersatz-Minisensor anthrazit	Spare Part

ORDERING INFORMATION

Art.-Nr.

4007841053949

E-Number

941200249

Typ

L 665 S anthrazit

neva
lux

nevalux AG
Neugrütstrasse 2
8610 Uster
+41 44 508 78 78
info@nevalux.swiss